

## G25

### Decorative LED Globe

EQUIVALENT TO 40 OR 60W INCANDESCENT



#### LOW POWER CONSUMPTION

*Save money and improve your energy efficiency with this low power consuming lamp that delivers BIG on light!*

#### OMINIDIRECTIONAL LIGHT

*Approximately 300° beam angle gives you smooth, clean light*

#### ENERGY STAR RATED

**SIMPLE, POWERFUL, FLEXIBLE** light that gives you illumination how and where you need it. This amazing little lamp gives you crisp clear light using only 4.5 or 6W of energy. Also, given it's omni-directional design you can count on maximum light in all the right areas.



#### OMNI-DIRECTIONAL

*Clear, crisp, even light for all your environments*

#### USES ONLY 4.5 or 6W ENERGY

*Energy efficient and contains no harmful chemicals like mercury and lead.*

#### ENERGY STAR RATED

*A rating you can trust for quality*



## ORDERING INFORMATION

FAMILY	PRODUCT	WATTAGE EQUIVALENT	COLOR TEMPERATURE	LENS	VOLTAGE	PACKAGING
LSPRO	G25	40WE	W27 - 2700K	LP FR - FROSTED	120 - 120VAC	BX - BOX
		60WE				

example: LSPRO G25 60WE W27 LP FR 120 BX

## PRODUCT NAME: LSPRO G25

SPECIFICATIONS <sup>1</sup>	W27	
Color Temperature <sup>2</sup>	2700K	
Equivalent Source Standard	40WE	60WE
Output (Lumens) <sup>3</sup>	350	560
Power Consumption	4.5W	6W
Power Factor	0.9	0.9
CRI	81	80
R9	6	1
Beam Angle	Omnidirectional (~ 300°)	
Input Voltage	120VAC	
Dimmable <sup>4</sup>	Yes	
Construction	Polymer	
Base	E26	
Dimensions (Length x Diameter)	4.61 x 3.3 in (117 x 83 mm)	
Weight	0.33 lbs (0.15 kg)	
Lumen Maintenance <sup>5</sup> (L <sub>70</sub> )	25,000	
Warranty	5 Year Limited	
Environment	Damp	
Certifications	Energy Star; RoHS; UL Listed	

### Dimmer Compatibility List:

**Lutron LED** - Skylark Contour® C-L CTCL-153P, Maestro® C-L MACL-153M, Maestro Wireless® C-L MRF2-6CL, Caséta Wireless® C-L PD-6WCL, Diva® C-L DVCL-153P, Ariadni® C-L AYCL-153P, Lumea® C-L LGCL-153P,

**Lutron Incand.** - Diva® DV-600P

**Leviton UNV** - SureSlide® 6674, SureSlide® 6672, IllumaTech® Slide IPL06-10Z

**Leviton ELV** - Decora® Rocker Slide DSE06-10Z

**Eaton-Cooper LED** - Aspire 9573

**Eaton-Cooper Incand.** - Aspire 9530

1 Specifications and values supplied are nominal and are subject to change without notification

2 Color temperatures conform to nominal CCTs as defined in ANSI Chromaticity Standard C78.377A

3 Lumen measurement complies with IES LM-79-08 testing procedures

4 Please see Dimmer Compatibility list for a list of compatible dimmers

5 Lumen maintenance calculations are based on measurements that comply with IES LM-80-08 testing procedures. L70 = 70% lumen maintenance, or when lamp reaches 70% of initial output