

# LED

## Panels

# PLT



### FEATURES

- USA approved LM-80 SMD
- UL LM79 certified
- Input Voltage: 100-277 VAC 50/60Hz
- THD:<20%(at 277V)
- High lumen output, high efficiency, energy saving up to 50%
- Standard Warranty: 5 Years
- Standard Lifetime: Designed to L70 minimum 50,000 hours
- UL# E485624



### 50% ENERGY EFFICIENCY & LONG LIFE

TYPICAL PAYBACK OF 1 - 3 YEARS

SKU #	Kelvin	Lumens	Size	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
-------	--------	--------	------	---------	---------	------	----------	------------	----------

<b>LEDF-10161</b>	<b>4000</b>	<b>5000</b>	<b>2X4</b>	<b>40</b>	<b>100-277</b>	<b>No</b>	<b>CEILING</b>	<b>50000</b>	<b>5 years</b>
-------------------	-------------	-------------	------------	-----------	----------------	-----------	----------------	--------------	----------------

## ADDITIONAL PHOTOS



## FEATURES

- Prismatic Lens
- Lightweight design
- LED driver included

## TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Office, Conference Rooms
- Hospitals

## WARRANTY

Warranty

5 Years

## SPECIFICATIONS

Dimmable ..... Yes  
 DLC Listed ..... No  
 Safety Rating ..... UL  
 CRI ..... 80  
 Color ..... Cool White  
 Color Temperature ..... 4000 Kelvin  
 Life Hours ..... 50,000  
 Wattage ..... 50 Watt  
 Lumens ..... 5000  
 Voltage ..... 100-277  
 Finish ..... White  
 Housing ..... Aluminum  
 Mounting ..... Ceiling Grid Mount/Suspended  
 Lens ..... Opaque  
 Length ..... 47.75 in.  
 Height ..... 1.9 in.  
 Width ..... 23.7 in.  
 Weight ..... 14 lbs.  
 Warranty ..... 5 Years



## PHOTOMETRICS

