

PARs Dimmable & Wet Rated

15W LED PAR38 RED FLOOD WET DIMMABLE

Item# 772500

Ordering Code LED15PAR38/FL/RED/D

UPC 739698777306

- Red PAR38 shape bulbs with medium E26 screw base, these bulbs are 15-Watt, fully dimmable 40-degree flood.
- 90-Watt equivalent LED light bulb.
- Smooth dimming, compatible with a variety of dimmers.
- Fully Dimmable and works with most dimmer switches
- Less maintenance, lasts about 12.5X longer than incandescent light bulbs.
- Wet rated, suitable for use with indoor and outdoor fixtures.
- Ideal for setting the mood at any event, whether it's holiday décor, festive parties, or showing support for a meaningful cause.
- 2 year Limited Warranty



Width	Height	Length
4.880 in	5.390 in	4.880 in



Technical Specifications			
Avg Hours	15000	M.O.L	5.110 in
Base	E26	Outer Carton Qty	24
Bulb Type	PAR38	Outer Carton UPC	407396987773068
Dimmable	Y	Safety Rated	UL
Enclosed Rated	Y	Safety Rating Type	WET
Energy Star	N	Title 20	Unregulated
Equivalent	90	Title 24	N
Individual Qty	1	Volts	120
Individual UPC	739698777306	Warranty Years	2
Item #	772500	Watts	15
M.O.D	4.720 in		



Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Tested Unit Item Number: 772505 Tested Unit Ordering Code: LED15PAR38/FL/PNK/D Related Item Number: 772500 Related Ordering Code: LED15PAR38/FL/RED/D Related Item Number: 772501 Related Ordering Code: LED15PAR38/FL/AMB/D	Related Item Number: 772502 Related Ordering Code: LED15PAR38/FL/YLW/D Related Item Number: 772503 Related Ordering Code: LED15PAR38/FL/GRN/D Related Item Number: 772504 Related Ordering Code: LED15PAR38/FL/BLU/D
---	---

	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum Tested*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	a IllumaTech	IPI06	Bad	1	6	Not smooth, flickers while dimming, flickers at lower outputs
		b SureSlide	6633-P	Good	1	6	Flickers at low outputs, dims completely
		c Vizia	VPI06-1LZ	Bad	1	6	Not smooth, flickers heavily while dimming and at low levels
	Lutron	d Toggler	TG-600	Best	1	6	Flickers slightly below 250lm, dims below 1%
		e Lumea	LGCL-600	Good	1	6	80% at MAX, flickers slightly below 250lm
		f Diva	DV-600	Best	1	6	Flickers slightly below 250lm, dims below 1%
		g Skylark	S-600	Best	1	6	Dims fully
	Legrand	h Maestro	MAW-600	Not Compatible	2	6	Not compatible w/1, dims fully w/>1, flickers slightly below 250lm
		i Titan	CD703-PW	Not Compatible	2	6	Not compatible w/1, dims fully w/>1, flickers slightly below 50lm
		j Harmony	D703-PTC	Not Compatible	2	6	Not compatible w/1, not smooth >1, flickers below 200lm
		k Harmony	H703-PTC	Not Compatible	3	6	Not compatible <3, flickers slightly below 100lm, dims fully
CFL/LED	Leviton	l IllumaTech	IPL06	Best	1	6	Flickers slightly below 120lm, dims completely
		m Sureslide	6674	Bad	1	6	Flickers significantly most levels below MAX
		n Decora	6672	Good	1	6	Flickers slightly at several positions below MAX, dims completely
	Lutron	o Decora Slide	DSL06-1LZ	Good	1	6	Flickers slightly at several positions below MAX, dims completely
		p Skylark	CTCL-153	Best	1	6	Dims completely
		q Diva	DVCL-153PL	Best	1	6	Dims completely
		r Maestro	MACL-153MLH	Best	1	6	Dims to 2%
		s Skylark	SCL-153P	Best	1	6	Dims to 3%
		t Toggler	TGCL-153PH	Best	1	6	Dims to 3%
		u Radio RA	RA2RR-6CL-PD	Best	1	6	Dims completely
		v Harmony	DCL453-PTC	Bad	1	6	Flickers at MAX w/>4, dims to 2%
		w Harmony	HCL453PTC	Best	1	6	Dims completely
		x Adorne Paddle	ADPD453LM2	Best	1	6	Dims to <1%
Electronic Low Voltage	Leviton	y Vizia	VPE04	Good	1	6	Not smooth, flickers slightly while dimming, dims completely
		z IllumaTech	IPE04	Not Compatible	1	6	
	Lutron	aa Decora	6615-P	Not Compatible	1	6	Dims to 35%
		ab Skylark Countour	CTELV-303P	Best	1	6	Dims completely
		ac Diva	DVELV-300P	Best	1	6	Dims completely
		ad Maestro	MAELV-600	Best	1	6	Dims completely
		ae Skylark	SELVB-300P	Good	1	6	HE dead travel (20%), dims completely
		af VIERTI	VTEL-600M-W	Best	1	6	Dims completely
		ag Scene Director	SCELV	Good	2	6	Flickers heavily @ MAX with 1, dims completely with >1
Magnetic Low Voltage	Leviton	ah Vizia	VPM-06	Good	1	6	Not smooth, flickers slightly while dimming, dims completely
		ai Decora	6613-P	Best	1	6	Flickers slightly below 100lm, dims completely
	Lutron	aj Maestro	MALV-600	Not Compatible	1	6	
		ak Harmony	DLV703-PW	Best	1	6	Flickers slightly below 100lm, dims completely
Legrand	al Titan	CDLV703-PW	Best	1	6	Flickers slightly below 65lm, dims completely	
	Smart Dimmer	am Leviton Decora Digital (Bluetooth)	DDMX1-BLZ	Best	1	6	Dims completely
an Leviton Decora Smart Z-Wave Technology		DZ6HD	Best	1	6	Dims completely	
ao Leviton Decora Smart WiFi Technology		DW1KD	Best	1	6	Dims completely	
ap Lutron Caseta Wireless smart dimmer Wi-Fi		PD-10NXD	Best	1	6	Dims to 6%	
aq Lutron Caseta Wireless smart dimmer Wi-Fi		PD-6WCL	Good	1	6	Not smooth, slight flicker while dimming, dims to 6%	
ar GE Z WAVE		ZW3005	Good	1	6	Flickers slightly at several positions below MAX, dims completely	
Universal	Legrand	as Adorne SofTap	ADTP703TU	Good	1	6	Not smooth, flickers while dimming, flickers below 50%, dims to 8%
		at Miro Decorator	DRD4-W	Good	1	6	Not smooth, flickers slightly while dimming, dims completely
		au Harmony	H703PTUTC	Not Compatible	1	6	Not compatible with 1, flickers at all levels below MAX w/ >1
		av Adorne Whisper	ADWR700MMTUM2	Best	1	6	Dims completely
	aw Adorne Touch	ADTH700MMTUM2	Good	1	6	Not smooth, flickers slightly while dimming, dims completely	
	Cooper	ax Decorator	DAL06P-C2-K-L	Bad	1	6	Not smooth, flickers while dimming, flickers at lower outputs
		ay Skye	SAL06P-W-K-L	Best	1	6	

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

*May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	Description
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (HE) Dead Travel Low End (LE) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.

©2025 Bulbrite Industries Inc.

All Rights Reserved.