

Dimmable Designer Elite LED PAR Lamps

Item Number

ENERGY STAR®

Item Description

Voltage

Lamp Watts

Lumens

Lumens Per Watt

*CBCP

Beam Angle

CCT

CRI

STK/MTD

Case Quantity

10W ELITE DESIGNER DIMMABLE PAR20 (REPLACES 60W)



LED10P20D24KFL	10W Smooth PAR20 - 2400K 40 Degree	120	10	600	60.0	1558	40	2400K	82	MTD	12
LED10P20D24KNFL	10W Smooth PAR20 - 2400K 25 Degree	120	10	600	60.0	3067	25	2400K	82	MTD	12
LED10P20D27KFL	10W Smooth PAR20 - 2700K 40 Degree	120	10	600	60.0	1558	40	2700K	82	STK	12
LED10P20D27KNFL	10W Smooth PAR20 - 2700K 25 Degree	120	10	600	60.0	3067	25	2700K	82	STK	12
LED10P20D30KFL	10W Smooth PAR20 - 3000K 40 Degree	120	10	650	65.0	1558	40	3000K	82	STK	12
LED10P20D30KNFL	10W Smooth PAR20 - 3000K 25 Degree	120	10	650	65.0	3067	25	3000K	82	STK	12
LED10P20D35KFL	10W Smooth PAR20 - 3500K 40 Degree	120	10	675	67.5	1558	40	3500K	82	MTD	12
LED10P20D35KNFL	10W Smooth PAR20 - 3500K 25 Degree	120	10	675	67.5	3067	25	3500K	82	MTD	12
LED10P20D41KFL	10W Smooth PAR20 - 4100K 40 Degree	120	10	700	70.0	1558	40	4100K	82	MTD	12
LED10P20D41KNFL	10W Smooth PAR20 - 4100K 25 Degree	120	10	700	70.0	3067	25	4100K	82	MTD	12
LED10P20D50KFL	10W Smooth PAR20 - 5000K 40 Degree	120	10	700	70.0	1558	40	5000K	82	MTD	12
LED10P20D50KNFL	10W Smooth PAR20 - 5000K 25 Degree	120	10	700	70.0	3067	25	5000K	82	MTD	12

8W ELITE DESIGNER DIMMABLE PAR20 (REPLACES 50W)

LED8P20D24KFL	8W Smooth PAR20 - 2400K 40 Degree	120	8	500	62.5	593	40	2400K	82	MTD	12
LED8P20D24KNFL	8W Smooth PAR20 - 2400K 25 Degree	120	8	500	62.5	1179	25	2400K	82	MTD	12
LED8P20D27KFL	8W Smooth PAR20 - 2700K 40 Degree	120	8	500	62.5	593	40	2700K	82	STK	12
LED8P20D27KNFL	8W Smooth PAR20 - 2700K 25 Degree	120	8	500	62.5	1179	25	2700K	82	STK	12
LED8P20D30KFL	★ 8W Smooth PAR20 - 3000K 40 Degree	120	8	515	64.4	593	40	3000K	82	STK	12
LED8P20D30KNFL	★ 8W Smooth PAR20 - 3000K 25 Degree	120	8	515	64.4	1179	25	3000K	82	STK	12
LED8P20D35KFL	8W Smooth PAR20 - 3500K 40 Degree	120	8	525	65.6	593	40	3500K	82	MTD	12
LED8P20D35KNFL	8W Smooth PAR20 - 3500K 25 Degree	120	8	525	65.6	1179	25	3500K	82	MTD	12
LED8P20D41KFL	8W Smooth PAR20 - 4100K 40 Degree	120	8	530	66.3	593	40	4100K	82	MTD	12
LED8P20D41KNFL	8W Smooth PAR20 - 4100K 25 Degree	120	8	530	66.3	1179	25	4100K	82	MTD	12
LED8P20D50KFL	8W Smooth PAR20 - 5000K 40 Degree	120	8	530	66.3	593	40	5000K	82	MTD	12
LED8P20D50KNFL	8W Smooth PAR20 - 5000K 25 Degree	120	8	530	66.3	1179	25	5000K	82	MTD	12

19W DIMMABLE PAR38 WET LOCATION (REPLACES 120W)



LED19E26P3827KFLWL	19W PAR38 - 2700K 40 Degree	120	19	1200	63.2	2231	40	2700K	82	STK	12
LED19E26P3830KFLWL	19W PAR38 - 3000K 40 Degree	120	19	1300	68.4	2364	40	3000K	82	STK	12

23W NON DIMMABLE PAR38 (REPLACES 150W)



LED23E26PAR3827KSPND	23W PAR38 - 2700K 15 Degree	120	23	1700	73.9	11517	15	2700K	82	MTD	12
LED23E26PAR3827KNFLND	23W PAR38 - 2700K 25 Degree	120	23	1700	73.9	1198	25	2700K	82	MTD	12
LED23E26PAR3827KFLND	23W PAR38 - 2700K 40 Degree	120	23	1700	73.9	2716	40	2700K	82	MTD	12
LED23E26PAR3830KSPND	23W PAR38 - 3000K 15 Degree	120	23	1700	73.9	12518	15	3000K	82	STK	12
LED23E26PAR3830KNFLND	23W PAR38 - 3000K 25 Degree	120	23	1700	73.9	7824	25	3000K	82	STK	12
LED23E26PAR3830KFLND	23W PAR38 - 3000K 40 Degree	120	23	1700	73.9	2952	40	3000K	82	STK	12
LED23E26PAR3841KSPND	23W PAR38 - 4100K 15 Degree	120	23	1700	73.9	13269	15	4100K	82	MTD	12
LED23E26PAR3841KNFLND	23W PAR38 - 4100K 25 Degree	120	23	1700	73.9	8293	25	4100K	82	MTD	12
LED23E26PAR3841KFLND	23W PAR38 - 4100K 40 Degree	120	23	1700	73.9	3130	40	4100K	82	MTD	12

★ ENERGY STAR® Rated (at time of print)



5 YEAR WARRANTY

*Minimum CBCP est. Consult tcp.com for most current photometry and LM79 data.