



LED PL Lamps - Hybrid

DESCRIPTION

Reduce your energy costs by replacing CFL PL lamps with these more efficient hybrid LED PL lamps that can operate with or without a ballast.

FEATURES

- Frosted lens reduces visual glare
- Delivers up to 145 Lumens per Watt for highly efficient performance
- Replaces up to a 13W CFL lamp
- Universal burn position
- No rewiring or modifications of any kind required for plug-and-play (Type A) operation; must be used with a compatible ballast, see installation sheet for full list of compatible ballasts
- Can operate directly off line voltage for ballast bypass (Type B) operation; ballast must be removed and fixture rewired during installation; see installation instructions for more information
- Only operates on magnetic ballasts listed in compatibility list. See installation sheet for full list of compatible ballasts

LISTINGS

- UL Listed for damp locations
- IP20
- FCC Part 15 Class B
- RoHS

PERFORMANCE

- CRI: 80
- CCT: 4000K
- LED L70 Life Hours: 50,000 hours

THERMAL

- - 4°F to 113°F (-20°C to 45°C) operating temperature

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



LISTED



RoHS
Compliant

WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Recessed Cans
- Ceiling Fixtures
- Wall Sconces

PERFORMANCE	Power Consumption	5, 7 Watt
	Lumens	721, 976
	Efficacy (LPW)	139, 145
	CRI	80
	CCT	4000K
	LED L70 Life Hours	50,000
ELECTRICAL	Input Voltage	120-277V
	THD	20%
	Power Factor	0.9
	Surge Protection	500V
	Burn Position	Universal
CONSTRUCTION	Shape	PL
	Base	G24D
	Lens	Plastic
	Finish	Frosted
LISTINGS	Certifications	UL Listed, IP20
	Material Usage	
	Environment	Damp Locations

* See Selectable Table for full breakdown

PERFORMANCE SUMMARY

Item #	Base*	Wattage	Lumens	LPW	CCT	Voltage	Replaces	CRI	Finish	LED L70 Life Hours	Dimmable	Burn Position
PLT-20326	GX23	7	976	139	4000K	120-277V	13W CFL	80	Frosted	50,000	No	Universal
PLT-20327	G23	5	721	145	4000K	120-277V	7 to 9W CFL	80	Frosted	50,000	No	Universal
PLT-20328	G24D	7	976	139	4000K	120-277V	13W CFL	80	Frosted	50,000	No	Universal
PLT-20329	G24D	5	721	145	4000K	120-277V	7 to 9W CFL	80	Frosted	50,000	No	Universal

*See Compatible Sockets for a full breakdown

COMPATIBLE SOCKETS

SKU	Compatible Sockets	Non-Compatible Sockets
PLT-20326	GX23	n/a
PLT-20327	G23	n/a
PLT-20328	G24-d, G24q, GX24d, GX24q	G24q-5/6/7, GX24q-5/6/7
PLT-20329	G24-d, G24q, GX24d, GX24q	G24q-5/6/7, GX24q-5/6/7

DIMENSIONS


PLT-20326

Height – 4.76"
Diameter – 1.52"




PLT-20327

Height – 4.13"
Diameter – 1.52"




PLT-20328

Height – 4.53"
Diameter – 1.52"



PLT-20329

Height – 3.9"
Diameter – 1.52"



WARNINGS

- Not for use with dimmers
- Not for use in enclosed fixtures.