

Series SKD

2"W Low Profile LED Surface Mount



FEATURES & SPECIFICATIONS

INTENDED USE

Full body micro silhouette makes a bold statement with a minimal design in brushed nickel powder coated finish (consult factory for other finishes). Scaled to the LED module the matte white diffuser surrounds the LEDs for soft lighting. Brushed nickel fixture can be surface mounted on wall or ceiling or pendant mounted with specially engineering cable mounting kit.

SIZE L x W x D in inches

- 22.5" or 46" or 92"L x 2"W x 2.6"D
- 22.5" or 46" or 92"L x 3"W x 3"D

MATERIALS & FEATURES

- Fully assembled housing is formed and welded, 22 gauge steel, chemically treated to resist corrosion and enhance paint adhesion
- Available in brushed nickel. Consult for other finishes
- Available with smooth frosted lens
- Clean body - No knock-outs on sides or ends
- Knock-outs on back accept standard electrical fittings (by others) Consult factory for other locations
- Dimming ballast options available (consult factory for availability and system compatibility)



MOUNTING

Surface mount or Pendant mount.
Horizontal or Vertical.

TYPICAL OPTIONS AND ACCESSORIES

Whips, hanging kits, and cord sets. See options page at the end of the T02Strip section, or contact factory for more details.

ACCESSORIES

- SKD-HC301WH - 5' cable kit w/white canopy*
- SKD-HC301BN - 5' cable kit w/brushed nickel*
- SKD-HC501BN - 4' Cable Mounting Kit*

*Includes canopy for cable only and a canopy for cable & power chord.

ORDERING INFORMATION

2FT - STANDARD

Example: SKDFR24LE12W1200LDMV40KWH

SKD	FR	24L	E12W1200L	DMV	40K	WH	
Series		Width	Wattage and Lumen		Color Temperature	Finish	
SKD Low Profile LED Surface Mount 2" Width Body		24L 22.5"	E12W1200L 12 System Watts, 1200 Delivered Lumens		30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH White BN Brushed Nickel BK Black BZ Bronze	
	Lens			Driver			Options
	FR Frosted Smooth			DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire			WP 6 ft. 3 wire 18 gauge whip CS 8ft. 3/18 3 prong (5-15P) cord & plug

2FT - HIGH OUTPUT

SKD	FR	24L	H18W1750L	DMV	40K	WH	
Series		Width	Wattage and Lumen		Color Temperature	Finish	
SKD Low Profile LED Surface Mount 2" Width Body		24L 24"	H18W1750L 18 System Watts, 1750 Delivered Lumens		30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH White BN Brushed Nickel BK Black BZ Bronze	
	Lens			Driver			Options
	FR Frosted Smooth			DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire			WP 6 ft. 3 wire 18 gauge whip CS 8ft. 3/18 3 prong (5-15P) cord & plug

SKD-HC301WH - 5' cable kit w/white canopy*
SKD-HC301BN - 5' cable kit w/brushed nickel*
SKD-HC501BN - 4' Cable Mounting Kit*

*Includes canopy for cable only and a canopy for cable & power chord.



Series SKD

3"W Low Profile LED Surface Mount



4FT - STANDARD

Example: SKDWB MW 48L E48W4800L DMV 40K BN

SKDWB	MW	48L	E48W4800L	DMV	40K	BN
Series		Size	Wattage and Lumen		Color Temperature	Finish
SKDWB		48L 46"	E32W3450L 32 System Watts, 3450 Delivered Lumens		30K 3000K	WH White
Low Profile LED Surface Mount			E48W4800L 48 System Watts, 4800 Delivered Lumens		35K 3500K	BN Brushed Nickel
3" Width Body			E57W5400L 57 System Watts, 5400 Delivered Lumens		40K 4000K	BK Black
					50K 5000K	BZ Bronze
	Lens			Driver		Options
	MW White Lens			DMV 0-10V Dimming	WP 6 ft. 3 wire 18 gauge whip	
	FR Frosted Lens			*Field installed-Dimming Wire	CS 8ft. 3/18 3 prong (5-15P) cord & plug	
				DMVFID 0-10V Dimming		
				*Factory installed-Dimming Wire		

4FT - HIGH OUTPUT

SKDWB	MW	48L	R72W7000L	DMV	40K	BN
Series		Size	Wattage and Lumen		Color Temperature	Finish
SKDWB		48L 46"	R72W7000L 72 System Watts, 7000 Delivered Lumens		30K 3000K	WH White
Low Profile LED Surface Mount					35K 3500K	BN Brushed Nickel
3" Width Body					40K 4000K	BK Black
					50K 5000K	BZ Bronze
	Lens			Driver		Options
	MW White Lens			DMV 0-10V Dimming	WP 6 ft. 3 wire 18 gauge whip	
	FR Frosted Lens			*Field installed-Dimming Wire	CS 8ft. 3/18 3 prong (5-15P) cord & plug	
				DMVFID 0-10V Dimming		
				*Factory installed-Dimming Wire		

8FT - STANDARD

SKDWB	MW	96L	E114W10800L	DMV	40K	BN
Series		Size	Wattage and Lumen		Color Temperature	Finish
SKDWB		96L 92"	H80W8000L 80 System Watts, 8000 Delivered Lumens		30K 3000K	WH White
Low Profile LED Surface Mount			E114W10800L 114 System Watts, 10800 Delivered Lumens		35K 3500K	BN Brushed Nickel
3" Width Body					40K 4000K	BK Black
					50K 5000K	BZ Bronze
	Lens			Driver		Options
	MW White Lens			DMV 0-10V Dimming	WP 6 ft. 3 wire 18 gauge whip	
	FR Frosted Lens			*Field installed-Dimming Wire	CS 8ft. 3/18 3 prong (5-15P) cord & plug	
				DMVFID 0-10V Dimming		
				*Factory installed-Dimming Wire		

8FT - HIGH OUTPUT

SKDWB	MW	96L	R144W14000L	DMV	40K	BN
Series		Size	Wattage and Lumen		Color Temperature	Finish
SKDWB		96L 92"	R144W14000L 144 System Watts, 14000 Delivered Lumens		30K 3000K	WH White
Low Profile LED Surface Mount					35K 3500K	BN Brushed Nickel
3" Width Body					40K 4000K	BK Black
					50K 5000K	BZ Bronze
	Lens			Driver		Options
	MW White Lens			DMV 0-10V Dimming	WP 6 ft. 3 wire 18 gauge whip	
	FR Frosted Lens			*Field installed-Dimming Wire	CS 8ft. 3/18 3 prong (5-15P) cord & plug	
				DMVFID 0-10V Dimming		
				*Factory installed-Dimming Wire		



Series SKD

Low Profile LED Surface Mount

PLT

DIMENSIONS

All dimensions are inches.

Specifications subject to change without notice.

