INTRODUCING...

BUILT FOR ULTIMATE PERFORMANCE



- Heavy duty applications
 - Truck fleets
 - Power tailgates
- First Responder
 - Police
 - Fire
 - Ambulance
 - Border Patrol
- RV
- Marine
- High demand automotive

- Cutting edge pure lead AGM technology
- All acid is absorbed in glass mat (zero free flowing liquid) no potential for freezing
- High compression cell structure improves high vibration resistance, 28X MORE than conventional batteries
- 3 Stage Terminal compression that eliminates potential leakage
- Ultra thin plate technology increases the number of plates creating greater exposure to reactive elements increasing performance
- Delivers exceptional CCA and reserve capacity
- Longer lifetime, no matter what you drive or where you drive it
- Quick starting every time

- Unrivalled cycling
- High vibration tolerance
- Resistance to gasoline and oils
- Faster recharge than conventional batteries
- Minimal maintenance even in extreme conditions
- OEM fit is ensured to be built to exact BCI standards
- Non-hazardous for ground, sea and air transport
- 2 year shelf life
- Longest warranty in the industry (4 years for AGM engine start batteries; 3 years for Marine AGM batteries)



DRAKONI BUILT FOR ULTIMATE PERFORMANCE

High Performance Pure Lead AGM Engine Start Battery • Non-Spillable • Maintenance Free



UPG No. 40882



UPG No. 40883



UPG No. 40884

	UPG No. 40882	UPG No. 40883	UPG No. 40884
BCI Group Number	31	65	34/78
Height with Terminal	9.25 in	7.44 in	7.76 in
Width	6.77 in	7.32 in	7.01 in
Length with Rib	12.91 in	11.77 in	10.87 in
Weight	76 l bs	55 l bs	50 l bs
Terminal Configuration	Threaded	SAE	Side
Pulse Cranking Amps	2,150 A	1,750 A	1,500 A
CA/MCA Rating at 32°F	1,370 A	1,070 A	1,050 A
Cold Cranking Amps at 0°F	1,150 A	930 A	880 A
Cold Cranking Amps at -20°F	900 A	650 A	585 A
Reserve Capacity	220 min	135 min	133 min
Capacity - 20 Hour Rate	102 Ah	69 Ah	64 Ah
Capacity - 10 Hour Rate	97 Ah	63 Ah	61 Ah
Internal Resistance	2.2 m Ω	3.3 m Ω	3.6 m Ω
Short Circuit Current	5,000 A	5,000 A	3,100 A
Warranty	4 years full	4 years full	4 years fu ll



PRAKON

BUILT FOR ULTIMATE PERFORMANCE
High Performance Pure Lead AGM Marine Battery • Non-Spillable • Maintenance Free



UPG No. 40880



UPG No. 40881

	UPG No. 40880	UPG No. 40881
BCI Group Number	24M	27M
Height with Terminal	8.74 in	8.74 in
Width	6.77 in	6.77 in
Length with Rib	10.87 in	12.44 in
Weight	58 l bs	68 lbs
Terminal Configuration	Marine	Marine
Pulse Cranking Amps	1,500 A	1,750 A
CA/MCA Rating at 32°F	1,010 A	1,080 A
Cold Cranking Amps at 0°F	840 A	930 A
Cold Cranking Amps at -20°F	590 A	650 A
Reserve Capacity	160 min	195 min
Capacity - 20 Hour Rate	76 Ah	91 Ah
Capacity - 10 Hour Rate	73 Ah	88 Ah
Internal Resistance	3.0 m Ω	2.6 m Ω
Short Circuit Current	3,100 A	5,000 A
Warranty	3 years fu ll	3 years fu ll