

## Filaments

2.5W LED CA10 2100K FILAMENT NOSTALGIC E12  
FULLY COMPATIBLE DIMMING

Item# 776903

Ordering Code LED2CA10/21K/FIL-NOS/3

UPC 739698769035

- CA10 LED bulb with an E12, 0, base in a Antique finish.
- 25 Watt equivalent, using only 2.5 Watts (160 lumens).
- 2100K color temperature for an Amber light.
- Fully Dimmable and works with most dimmer switches.
- Damp Rated for use in indoor / outdoor (not directly exposed to water) locations.
- Long lasting energy efficient LED lighting, lasts up to 15,000 hours.
- 5 year Limited Lifetime Warranty



Width	Height	Length
1.5 in	5.14 in	1.5 in



### Technical Specifications

<b>Avg Hours</b>	15000	<b>Inner Carton UPC</b>	10739698769032
<b>Base</b>	E12	<b>Item #</b>	776903
<b>Beam Angle(°)</b>	300	<b>Lumens</b>	160
<b>Bulb Type</b>	CA10	<b>M.O.D</b>	1.26 in
<b>CBCP</b>	0	<b>M.O.L</b>	4.33 in
<b>CCT Color</b>	2100K	<b>Max Op Temp</b>	40 C
<b>Color</b>	Amber Light	<b>Min Op Temp</b>	-20 C
<b>CRI</b>	90	<b>Outer Carton Qty</b>	1
<b>Dimmable</b>	Y	<b>Outer Carton UPC</b>	40739698769033
<b>Enclosed Rated</b>	Y	<b>Safety Rated</b>	UL
<b>Energy Star</b>	N	<b>Safety Rating Type</b>	Damp
<b>Equivalent</b>	25W	<b>Title 20</b>	U
<b>Finish</b>	Antique	<b>Title 24</b>	N
<b>Individual Qty</b>	1	<b>Volts</b>	120
<b>Individual UPC</b>	739698769035	<b>Warranty Years</b>	5
<b>Inner Carton Qty</b>	10	<b>Watts</b>	2.5



145 West Commercial Ave.  
Moonachie, NJ 07074

### Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

**Product Family Name:**  
**Item Number:** 776903  
**Ordering Code:** LED2CA10/21K/FIL-NOS/3  
**Item Number:**  
**Ordering Code:**

	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum Tested*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	IlumaTech	IPI06	Good	2	6	Flickering at HE with 1
		SureSlide	6633-P	Good	2	6	Flickering at HE with 1
		Vizia	VPI06-1LZ	Not compatible	1	6	Not turn off with 1-6
	Lutron	Toggle	TG-600	Good	2	6	Flickering at HE with 1
		Lumea	LGCL-600	Best	1	6	Dims down to 1%
		Divi	DV-600	Best	1	6	Dims down to 1%
		Skylark	S-600	Best	1	6	Dims down to 1%
		Maestro	MAW-600	Not compatible	1	6	Not turn on with 1-6
	Legrand	Titan	CD703-PW	Bad	5	6	Not smooth dimming
		Harmony	D703-PTC	Bad	6	6	Not smooth dimming
		Harmony	H703-PTC	Bad	6	6	Not smooth dimming
	CFL/LED	Leviton	IlumaTech	IPI06	Good	2	6
SureSlide			6674	Good	2	6	Dims down to 1%
Decora			6672	Good	2	6	Dims down to 1%
Decora Slide			DSL06-1LZ	Good	2	6	Dims down to 1%
Lutron		Skylark	CTCL-153	Good	2	6	Dims down to 1%
		Sunnata	STCL-153	Best	2	6	Dims down to 1%
		Divi	DVCL-153PL	Good	2	6	Dims down to 1%
		Maestro	MACL-153MLH	Best	1	6	Dims down to 1%
		Skylark	SCL-153P	Good	2	6	Dims down to 1%
		Toggle	TGCL-153PH	Good	2	6	Dims down to 1%
		Radio RA	RA2RR-6CL-PD	Good	2	6	Dims down to 1%
		Harmony	DCL453-PTC	Good	2	6	Dims down to 1%
		Radiant	RHCL453PW	Good	2	6	Dims down to 1%
		Adorne Paddle	ADPD453LM2	Best	1	6	Dims down to 1%
Legrand		Vizia	VPE04	Good	1	6	Dims down to 1%, shimmer at LE with 1-6
		IlumaTech	IPE04	Bad	1	6	Dims down to 20%, shimmer at LE with 1-6
		Decora	6615-P	Not compatible	1	6	No dimming range 1-6
		Skylark Countour	CTELV-303P	Good	1	6	Dims down to 1%, shimmer at LE with 1-6
	Divi	DVELV-300P	Good	1	6	Dims down to 1%, shimmer at LE with 1-6	
	Maestro	MAELV-600	Good	1	6	Dims down to 1%, shimmer at LE with 1-6	
	Skylark	SELV-300P	Good	1	6	Dims down to 1%, shimmer at LE with 1-6	
Legrand	VIERTI	VTEL-600M-W	Good	1	6	Dims down to 1%, shimmer at LE with 1-6	
	Scene Director	SCELV	Bad	1	6	Flickering at HE with 1-6	
Magnetic Low Voltage	Leviton	Vizia	VPM-06	Not compatible	1	6	Not turn off with 1-6
		Decora	6613-P	Good	1	6	Dims down to 1%, not smooth dimming
	Lutron	Maestro	MALV-600	Not compatible	1	6	Not turn off with 1-6
		Harmony	DLV703-PW	Good	3	6	Dims down to 1%
Legrand	Titan	CDLV703-PW	Good	4	6	dims down to 1%	
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMX1-BLZ	Best	1	6	Dims down to 1%
	Leviton	Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	Dims down to 1%
	Leviton	Decora Smart WiFi Technology	DW1KD	Best	1	6	Dims down to 1%
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-10NXd	Best	1	6	Dims down to 1%
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Good	2	6	Dims down to 1%
	GE	Z WAVE	ZW3005	Best	1	6	Dims down to 1%
Universal	Legrand	Adorne SoftTap	ADTP703TU	Bad	4	6	Dims down to 6%, flashing once when the dimmer slid to HE
		Miro Decorator	DRD4-W	Good	1	6	Flashing once when the dimmer slid to HE,
		Harmony	H703PTUTC	Bad	4	6	Flickering at LE with 4-6
		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Dims down to 1%
	Cooper	Adorne Touch	ADTH700MMTUM2	Best	1	6	Dims down to 1%
		Decorator	DAL06P-CZ-K-L	Good	2	6	Dims down to 1%
		Skye	SAL06P-W-K-L	Good	2	6	Dims down to 1%

\*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.  
 †May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

<b>Overall Rating</b>	
<b>Not Compatible</b>	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
<b>Bad</b>	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
<b>Good</b>	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
<b>Best</b>	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
<b>High End (H.E.) Dead Travel</b>	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
<b>Low End (L.E.) Dead Travel</b>	

Contact Information:  
 Bulbrite Industries Inc.  
 145 West Commercial Avenue  
 Moonachie, New Jersey 07074  
 PHONE: 1-800-528-9555  
 FAX: 1-800-441-7708  
 Email: ProductSupport@bulbrite.com  
 Bulbrite Industries Inc.  
 All Rights Reserved.