



# LED PAR Lamps

**DIMMABLE • WET LOCATION • 25,000 HOURS**

TCP's award winning PAR lamps combine traditional beauty with top-notch technology. With the wide variety of options available—you can be sure to find the PAR lamps to meet your needs.

## LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Track lights
- Display lights
- Outdoor fixtures that protect lamps from the elements
- Recessed downlights
- Flood and spotlighting

### FEATURES

- Up to 85% less energy than halogen alternatives
- Long life
- Unique full face optics
- Very low heat generation
- Excellent color consistency and CRI
- Light weight
- UL approved for wet location
- Smooth clean outside housing
- Durable plastic

### BENEFITS

- Instant energy savings
- Minimizes replacement and maintenance costs
- Provides designer grade light quality with same look as halogen replacements
- Perfect for sensitive display lighting such as art galleries
- Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp
- Track or downlight installations are not strained by excess weight
- Suitable for wet locations—when exposed to water use only with device base up
- Seamlessly blends into lighting applications
- Lowers the risk for injury or breakage

## SPECIFICATIONS

Color Temperatures.....2400K, 2700K, 3000K, 3500K, 4100K, 5000K  
 Wattage Replacements..... 50W, 60W, 75W, 90W, 120W, 150W  
 Input Line Voltage ..... 120 VAC  
 Input Line Frequency..... 50/60HZ  
 Lamp Life (Rated) .....25,000 hours  
 Minimum Starting Temp .....-30C  
 Maximum Operating Temp..... 45°C  
 CRI.....80



**5 YEAR WARRANTY**  
 \* Based on 12 hours use per day



Approved for enclosed fixtures however completely sealed fixture applications (ex: in ground landscape fixtures) may reduce life.



LED  
 we know light.™





# LED PAR Lamps

**DIMMABLE • WET LOCATION • 25,000 HOURS**

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

## LED PAR20 50W Equivalent Options

**7W PAR20 • Dimmable • 25,000 Hours • 3.5" (MOI) x 2.5" (DIA)**



LED8P20D24KFL	LED 7W P20 DIM 24KFL	7	550	78.6	2400K	80	—	40°
LED8P20D24KNFL	LED 7W P20 DIM 24KNFL	7	550	78.6	2400K	80	—	25°
LED8P20D27KFL	LED 7W P20 DIM 27KFL	7	600	85.7	2700K	80	1208	40°
LED8P20D27KFLB	LED 7W P20 DIM 27KFL BLACK	7	600	85.7	2700K	80	1208	40°
LED8P20D27KNFL	LED 7W P20 DIM 27KNFL	7	600	85.7	2700K	80	2030	25°
LED8P20D27KNFLB	LED 7W P20 DIM 27KNFL BLACK	7	600	85.7	2700K	80	2030	25°
LED8P20D27KSP	LED 7W P20 DIM 27KSP	7	600	85.7	2700K	80	4898	15°
LED8P20D30KFL	LED 7W P20 DIM 30KFL	7	625	89.3	3000K	80	1187	40°
LED8P20D30KFLB	LED 7W P20 DIM 30KFL BLACK	7	625	89.3	3000K	80	1187	40°
LED8P20D30KNFL	LED 7W P20 DIM 30KNFL	7	625	89.3	3000K	80	2050	25°
LED8P20D30KNFLB	LED 7W P20 DIM 30KNFL BLACK	7	625	89.3	3000K	80	2050	25°
LED8P20D30KSP	LED 7W P20 DIM 30KSP	7	625	89.3	3000K	80	5391	15°
LED8P20D35KFL	LED 7W P20 DIM 35KFL	7	675	96.4	3500K	80	1722	40°
LED8P20D35KNFL	LED 7W P20 DIM 35KNFL	7	675	96.4	3500K	80	4807	25°
LED8P20D41KFL	LED 7W P20 DIM 41KFL	7	675	96.4	4100K	80	1383	40°
LED8P20D41KFLB	LED 7W P20 DIM 41KFL BLACK	7	675	96.4	4100K	80	1383	40°
LED8P20D41KNFL	LED 7W P20 DIM 41KNFL	7	675	96.4	4100K	80	2174	25°
LED8P20D41KNFLB	LED 7W P20 DIM 41KNFL BLACK	7	675	96.4	4100K	80	2174	25°
LED8P20D41KSP	LED 7W P20 DIM 41KSP	7	675	96.4	4100K	80	5411	15°
LED8P20D50KFL	LED 7W P20 DIM 50KFL	7	700	100	5000K	80	1330	40°
LED8P20D50KFLB	LED 7W P20 DIM 50KFL BLACK	7	700	100	5000K	80	1330	40°
LED8P20D50KNFL	LED 7W P20 DIM 50KNFL	7	700	100	5000K	80	2172	25°
LED8P20D50KSP	LED 7W P20 DIM 50SP	7	700	100	5000K	80	5599	15°

## LED PAR30 60W Equivalent Options

**10W PAR30 Short Neck • Dimmable • 25,000 Hours • 3.5" (MOI) x 3.8" (DIA) PHASING OUT**



LED10P30SD27KFL	LED 10W P30 DIM 27KFL	10	720	72.0	2700K	80	1714	40°
LED10P30SD30KSP	LED 10W P30 DIM 30KSP	10	720	72.0	3000K	80	—	15°
LED10P30SD41KFL	LED 10W P30 DIM 41KFL	10	720	72.0	4100K	80	1847	40°

## LED PAR30 75W Equivalent Options

**10W PAR30 Short Neck • Dimmable • 25,000 Hours • 3.6" (MOI) x 3.8" (DIA)**



LED12P30SD24KFL	LED 10W P30SN DIM 24KFL	10	800	80.0	2400K	80	1619	40°
LED12P30SD24KNFL	LED 10W P30SN DIM 24KNFL	10	800	80.0	2400K	80	—	25°
LED12P30SD24KSP	LED 10W P30SN DIM 24KSP	10	800	80.0	2400K	80	—	15°
LED12P30SD27KFL	LED 10W P30SN DIM 27KFL	10	850	85.0	2700K	80	1817	40°
LED12P30SD27KFLB	LED 10W P30SN DIM 27KFL BLACK	10	850	85.0	2700K	80	1817	40°
LED12P30SD27KNFL	LED 10W P30SN DIM 27KNFL	10	850	85.0	2700K	80	4025	25°
LED12P30SD27KNFLB	LED 10W P30SN DIM 27KNFL BLACK	10	850	85.0	2700K	80	4025	25°
LED12P30SD27KSP	LED 10W P30SN DIM 27KSP	10	850	85.0	2700K	80	8042	15°
LED12P30SD30KFL	LED 10W P30SN DIM 30KFL	10	850	85.0	3000K	80	1858	40°
LED12P30SD30KFLB	LED 10W P30SN DIM 30KFL BLACK	10	850	85.0	3000K	80	1858	40°
LED12P30SD30KNFL	LED 10W P30SN DIM 30KNFL	10	850	85.0	3000K	80	4968	25°
LED12P30SD30KNFLB	LED 10W P30SN DIM 30KNFL BLACK	10	850	85.0	3000K	80	4968	25°
LED12P30SD30KSP	LED 10W P30SN DIM 30KSP	10	850	85.0	3000K	80	8380	15°
LED12P30SD30KSPB	LED 10W P30SN DIM 30KSP BLACK	10	850	85.0	3000K	80	8380	15°
LED12P30SD35KFL	LED 10W P30SN DIM 35KFL	10	850	85.0	3500K	80	2232	40°
LED12P30SD35KFLB	LED 10W P30SN DIM 35KFL BLACK	10	850	85.0	3500K	80	2232	40°

NOTE: All items come in shipping cartons of 12.

*continued next page*

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcp.com](http://tcp.com)



# LED PAR Lamps

**DIMMABLE • WET LOCATION • 25,000 HOURS**

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

## LED PAR30 75W Equivalent Options *continued*

### 10W PAR30 Short Neck • Dimmable • 25,000 Hours • 3.6" (MOI) x 3.8" (DIA)



LED12P30SD35KNFL	LED 10W P30SN DIM 35KNFL	10	850	85.0	3500K	80	4402	25°
LED12P30SD35KNFLB	LED 10W P30SN DIM 35KNFL BLACK	10	850	85.0	3500K	80	4402	25°
LED12P30SD35KSP	LED 10W P30SN DIM 35KSP	10	850	85.0	3500K	80	—	15°
LED12P30SD41KFL	LED 10W P30SN DIM 41KFL	10	850	85.0	4100K	80	2247	40°
LED12P30SD41KFLB	LED 10W P30SN DIM 41KFL BLACK	10	850	85.0	4100K	80	2247	40°
LED12P30SD41KNFL	LED 10W P30SN DIM 41KNFL	10	850	85.0	4100K	80	4895	25°
LED12P30SD41KSP	LED 10W P30SN DIM 41KSP	10	850	85.0	4100K	80	8710	15°
LED12P30SD50KFL	LED 10W P30SN DIM 50KFL	10	850	85.0	5000K	80	2454	40°
LED12P30SD50KNFL	LED 10W P30SN DIM 50KNFL	10	850	85.0	5000K	80	5260	25°
LED12P30SD50KSP	LED 10W P30SN DIM 50KSP	10	850	85.0	5000K	80	9292	15°

### 10.5W PAR30 • Dimmable • 25,000 Hours • 4.6" (MOI) x 3.8" (DIA)



LED12P30D24KFL	LED 10.5W P30 DIM 24KFL	10.5	800	76.2	2400K	80	—	40°
LED12P30D24KNFL	LED 10.5W P30 DIM 24KNFL	10.5	800	76.2	2400K	80	—	25°
LED12P30D24KSP	LED 10.5W P30 DIM 24KSP	10.5	800	76.2	2400K	80	—	15°
LED12P30D27KFL	LED 10.5W P30 DIM 27KFL	10.5	850	81.0	2700K	80	2202	40°
LED12P30D27KFLB	LED 10.5W P30 DIM 27KFL BLACK	10.5	850	81.0	2700K	80	2202	40°
LED12P30D27KNFL	LED 10.5W P30 DIM 27KNFL	10.5	850	81.0	2700K	80	5031	25°
LED12P30D27KNFLB	LED 10.5W P30 DIM 27KNFL BLACK	10.5	850	81.0	2700K	80	5031	25°
LED12P30D27KSP	LED 10.5W P30 DIM 27KSP	10.5	850	81.0	2700K	80	9193	15°
LED12P30D27KSPB	LED 10.5W P30 DIM 27KSP BLACK	10.5	850	81.0	2700K	80	9193	15°
LED12P30D30KFL	LED 10.5W P30 DIM 30KFL	10.5	850	81.0	3000K	80	2389	40°
LED12P30D30KFLB	LED 10.5W P30 DIM 30KFL BLACK	10.5	850	81.0	3000K	80	2389	40°
LED12P30D30KNFL	LED 10.5W P30 DIM 30KNFL	10.5	850	81.0	3000K	80	5528	25°
LED12P30D30KNFLB	LED 10.5W P30 DIM 30KNFL BLACK	10.5	850	81.0	3000K	80	5528	25°
LED12P30D30KSP	LED 10.5W P30 DIM 30KSP	10.5	850	81.0	3000K	80	9006	15°
LED12P30D30KSPB	LED 10.5W P30 DIM 30KSP BLACK	10.5	850	81.0	3000K	80	9006	15°
LED12P30D30KFL	LED 10.5W P30 DIM 35KFL	10.5	850	81.0	3500K	80	2362	40°
LED12P30D35KNFL	LED 10.5W P30 DIM 35KNFL	10.5	850	81.0	3500K	80	5029	25°
LED12P30D35KSP	LED 10.5W P30 DIM 35KSP	10.5	850	81.0	3500K	80	9735	15°
LED12P30D41KFL	LED 10.5W P30 DIM 41KFL	10.5	850	81.0	4100K	80	2561	40°
LED12P30D41KFLB	LED 10.5W P30 DIM 41KFL BLACK	10.5	850	81.0	4100K	80	2561	40°
LED12P30D41KNFL	LED 10.5W P30 DIM 41KNFL	10.5	850	81.0	4100K	80	5781	25°
LED12P30D41KNFLB	LED 10.5W P30 DIM 41KNFL BLACK	10.5	850	81.0	4100K	80	5781	25°
LED12P30D41KSP	LED 10.5W P30 DIM 41KSP	10.5	850	81.0	4100K	80	9491	15°
LED12P30D41KSPB	LED 10.5W P30 DIM 41KSP BLACK	10.5	850	81.0	4100K	80	9491	15°
LED12P30D50KFL	LED 10.5W P30 DIM 50KFL	10.5	850	81.0	5000K	80	2437	40°
LED12P30D50KFLB	LED 10.5W P30 DIM 50KFL BLACK	10.5	850	81.0	5000K	80	2437	40°
LED12P30D50KNFL	LED 10.5W P30 DIM 50KNFL	10.5	850	81.0	5000K	80	5575	25°
LED12P30D50KSP	LED 10.5W P30 DIM 50KSP	10.5	850	81.0	5000K	80	9647	15°

## LED PAR30 75W Equivalent Options

### 13.5W PAR30 • Dimmable • 25,000 Hours • 4.6" (MOI) x 3.8" (DIA)

LED14P30D24KFL	LED 13.5W P30 DIM 24KFL	13.5	1000	74.1	2400K	80	—	40°
LED14P30D24KNFL	LED 13.5W P30 DIM 24KNFL	13.5	1000	74.1	2400K	80	—	25°
LED14P30D24KNFLB	LED 13.5W P30 DIM 24KNFL BLACK	13.5	1000	74.1	2400K	80	—	25°
LED14P30D24KSP	LED 13.5W P30 DIM 24KSP	13.5	1000	74.1	2400K	80	—	15°
LED14P30D27KFL	LED 13.5W P30 DIM 27KFL	13.5	1050	77.8	2700K	80	2693	40°
LED14P30D27KFLB	LED 13.5W P30 DIM 27KFL BLACK	13.5	1050	77.8	2700K	80	2693	40°

NOTE: All items come in shipping cartons of 12.

*continued next page*

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)



# LED PAR Lamps

**DIMMABLE • WET LOCATION • 25,000 HOURS**

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

## LED PAR30 75W Equivalent Options *continued*

**13.5W PAR30 • Dimmable • 25,000 Hours • 4.6" (MOI) x 3.8" (DIA)**



LED14P30D27KNFL	LED 13.5W P30 DIM 27KNFL	13.5	1050	77.8	2700K	80	5808	25°
LED14P30D27KNFLB	LED 13.5W P30 DIM 27KNFL BLACK	13.5	1050	77.8	2700K	80	5808	25°
LED14P30D27KSP	LED 13.5W P30 DIM 27KSP	13.5	1050	77.8	2700K	80	10563	15°
LED14P30D27KSPB	LED 13.5W P30 DIM 27KSP BLACK	13.5	1050	77.8	2700K	80	10563	15°
LED14P30D30KFL	LED 13.5W P30 DIM 30KFL	13.5	1050	77.8	3000K	80	2849	40°
LED14P30D30KFLB	LED 13.5W P30 DIM 30KFLB	13.5	1050	77.8	3000K	80	2849	40°
LED14P30D30KNFL	LED 13.5W P30 DIM 30KNFL	13.5	1050	77.8	3000K	80	6392	25°
LED14P30D30KNFLB	LED 13.5W P30 DIM 30KNFL BLACK	13.5	1050	77.8	3000K	80	6392	25°
LED14P30D30KSP	LED 13.5W P30 DIM 30KSP	13.5	1050	77.8	3000K	80	11181	15°
LED14P30D30KSPB	LED 13.5W P30 DIM 30KSP BLACK	13.5	1050	77.8	3000K	80	11181	15°
LED14P30D35KFL	LED 13.5W P30 DIM 35KFL	13.5	1050	77.8	3500K	80	—	40°
LED14P30D35KFLB	LED 13.5W P30 DIM 35KFL BLACK	13.5	1050	77.8	3500K	80	—	40°
LED14P30D35KNFL	LED 13.5W P30 DIM 35KNFL	13.5	1050	77.8	3500K	80	—	25°
LED14P30D35KSP	LED 13.5W P30 DIM 35KSP	13.5	1050	77.8	3500K	80	—	15°
LED14P30D41KFL	LED 13.5W P30 DIM 41KFL	13.5	1050	77.8	4100K	80	2661	40°
LED14P30D41KFLB	LED 13.5W P30 DIM 41KFL BLACK	13.5	1050	77.8	4100K	80	2661	40°
LED14P30D41KNFL	LED 13.5W P30 DIM 41KNFL	13.5	1050	77.8	4100K	80	5781	25°
LED14P30D41KNFLB	LED 13.5W P30 DIM 41KNFL BLACK	13.5	1050	77.8	4100K	80	5781	25°
LED14P30D41KSP	LED 13.5W P30 DIM 41KSP	13.5	1050	77.8	4100K	80	12465	15°
LED14P30D41KSPB	LED 13.5W P30 DIM 41KSP BLACK	13.5	1050	77.8	4100K	80	12465	15°
LED14P30D50KFL	LED 13.5W P30 DIM 50KFL	13.5	1050	77.8	5000K	80	2837	40°
LED14P30D50KFLB	LED 13.5W P30 DIM 50KFL BLACK	13.5	1050	77.8	5000K	80	2837	40°
LED14P30D50KNFL	LED 13.5W P30 DIM 50KNFL	13.5	1050	77.8	5000K	80	5875	25°
LED14P30D50KSP	LED 13.5W P30 DIM 50KSP	13.5	1050	77.8	5000K	80	12073	15°

## LED PAR38 90W Equivalent Options

**13.5W PAR38 • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)**



LED14P38D24KFL	LED 13.5W P38 DIM 24KFL	13.5	1000	74.1	2400K	80	—	40°
LED14P38D24KNFL	LED 13.5W P38 DIM 24KNFL	13.5	1000	74.1	2400K	80	—	25°
LED14P38D24KSP	LED 13.5W P38 DIM 24KSP	13.5	1000	74.1	2400K	80	—	15°
LED14P38D27KFL	LED 13.5W P38 DIM 27KFL	13.5	1050	77.8	2700K	80	2480	40°
LED14P38D27KNFL	LED 13.5W P38 DIM 27KNFL	13.5	1050	77.8	2700K	80	7649	25°
LED14P38D27KNFLB	LED 13.5W P38 DIM 27KNFL BLACK	13.5	1050	77.8	2700K	80	7649	25°
LED14P38D27KSP	LED 13.5W P38 DIM 27KSP	13.5	1050	77.8	2700K	80	12073	15°
LED14P38D27KSPB	LED 13.5W P38 DIM 27KSP BLACK	13.5	1050	77.8	2700K	80	12073	15°
LED14P38D30KFL	LED 13.5W P38 DIM 30KFL	13.5	1050	77.8	3000K	80	2498	40°
LED14P38D30KNFL	LED 13.5W P38 DIM 30KNFL	13.5	1050	77.8	3000K	80	7606	25°
LED14P38D30KSP	LED 13.5W P38 DIM 30KSP	13.5	1050	77.8	3000K	80	11845	15°
LED14P38D30KWFL	LED 13.5W P38 DIM 30KWFL	13.5	1050	77.8	3000K	80	—	60°
LED14P38D35KFL	LED 13.5W P38 DIM 35KFL	13.5	1050	77.8	3500K	80	2736	40°
LED14P38D35KFLB	LED 13.5W P38 DIM 35KFL BLACK	13.5	1050	77.8	3500K	80	2736	40°
LED14P38D35KNFL	LED 13.5W P38 DIM 35KNFL	13.5	1050	77.8	3500K	80	—	25°
LED14P38D35KSP	LED 13.5W P38 DIM 35KSP	13.5	1050	77.8	3500K	80	12856	15°
LED14P38D41KFL	LED 13.5W P38 DIM 41KFL	13.5	1050	77.8	4100K	80	2678	40°
LED14P38D41KFLB	LED 13.5W P38 DIM 41KFL BLACK	13.5	1050	77.8	4100K	80	2678	40°
LED14P38D41KNFL	LED 13.5W P38 DIM 41KNFL	13.5	1050	77.8	4100K	80	8310	25°
LED14P38D41KSP	LED 13.5W P38 DIM 41KSP	13.5	1050	77.8	4100K	80	13535	15°
LED14P38D41KSPB	LED 13.5W P38 DIM 41KSP BLACK	13.5	1050	77.8	4100K	80	13535	15°
LED14P38D50KFL	LED 13.5W P38 DIM 50KFL	13.5	1050	77.8	5000K	80	2647	40°

NOTE: All items come in shipping cartons of 12.

*continued next page*

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)



# LED PAR Lamps

**DIMMABLE • WET LOCATION • 25,000 HOURS**

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

## LED PAR38 90W Equivalent Options *continued*

### 13.5W PAR38 • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)

LED14P38D50KFLB	LED 13.5W P38 DIM 50KFL BLACK	13.5	1050	77.8	5000K	80	2647	40°
LED14P38D50KNFL	LED 13.5W P38 DIM 50KNFL	13.5	1050	77.8	5000K	80	8071	25°
LED14P38D50KSP	LED 13.5W P38 DIM 50KSP	13.5	1050	77.8	5000K	80	12418	15°

## LED PAR38 120W Equivalent Options

### 15W PAR38 • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)



LED17P38D24KFL	LED 15W P38 DIM 24KFL	15	1050	70.0	2400K	80	—	40°
LED17P38D24KNFL	LED 15W P38 DIM 24KNFL	15	1050	70.0	2400K	80	—	25°
LED17P38D24KSP	LED 15W P38 DIM 24KSP	15	1050	70.0	2400K	80	—	15°
LED17P38D27KFL	LED 15W P38 DIM 27KFL	15	1200	80.0	2700K	80	2757	40°
LED17P38D27KFLB	LED 15W P38 DIM 27KFL BLACK	15	1200	80.0	2700K	80	2757	40°
LED17P38D27KNFL	LED 15W P38 DIM 27KNFL	15	1200	80.0	2700K	80	8857	25°
LED17P38D27KSP	LED 15W P38 DIM 27KSP	15	1200	80.0	2700K	80	16239	15°
LED17P38D30KFL	LED 15W P38 DIM 30KFL	15	1200	80.0	3000K	80	3106	40°
LED17P38D30KFLB	LED 15W P38 DIM 30KFL BLACK	15	1200	80.0	3000K	80	3106	40°
LED17P38D30KNFL	LED 15W P38 DIM 30KNFL	15	1200	80.0	3000K	80	9274	25°
LED17P38D30KNFLB	LED 15W P38 DIM 30KNFL BLACK	15	1200	80.0	3000K	80	9274	25°
LED17P38D30KSP	LED 15W P38 DIM 30KSP	15	1200	80.0	3000K	80	18492	15°
LED17P38D30KSPB	LED 15W P38 DIM 30KSP BLACK	15	1200	80.0	3000K	80	18492	15°
LED17P38D30KWFLB	LED 15W P38 DIM 30KWFL BLACK	15	1200	80.0	3000K	80	—	60°
LED17P38D35KFL	LED 15W P38 DIM 35KFL	15	1200	80.0	3500K	80	2994	40°
LED17P38D35KFLB	LED 15W P38 DIM 35KFL BLACK	15	1200	80.0	3500K	80	2994	40°
LED17P38D35KNFL	LED 15W P38 DIM 35KNFL	15	1200	80.0	3500K	80	9405	25°
LED17P38D35KNFLB	LED 15W P38 DIM 35KNFL BLACK	15	1200	80.0	3500K	80	9405	25°
LED17P38D35KSP	LED 15W P38 DIM 35KSP	15	1200	80.0	3500K	80	18094	15°
LED17P38D41KFL	LED 15W P38 DIM 41KFL	15	1200	80.0	4100K	80	2870	40°
LED17P38D41KFLB	LED 15W P38 DIM 41KFL BLACK	15	1200	80.0	4100K	80	2870	40°
LED17P38D41KNFL	LED 15W P38 DIM 41KNFL	15	1200	80.0	4100K	80	9288	25°
LED17P38D41KNFLB	LED 15W P38 DIM 41KNFL BLACK	15	1200	80.0	4100K	80	9288	25°
LED17P38D41KSP	LED 15W P38 DIM 41KSP	15	1200	80.0	4100K	80	18408	15°
LED17P38D41KSPB	LED 15W P38 DIM 41KSP BLACK	15	1200	80.0	4100K	80	18408	15°
LED17P38D50KFL	LED 15W P38 DIM 50KFL	15	1200	80.0	5000K	80	2713	40°
LED17P38D50KFLB	LED 15W P38 DIM 50KFL BLACK	15	1200	80.0	5000K	80	2713	40°
LED17P38D50KNFL	LED 15W P38 DIM 50KNFL	15	1200	80.0	5000K	80	9387	25°
LED17P38D50KSP	LED 15W P38 DIM 50KSP	15	1200	80.0	5000K	80	19721	15°

## LED PAR38 HIGH OUTPUT 150W Equivalent Options

### 18.5W PAR38 High Output • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)

LED17HOP38D27KFL	LED 18.5W HOP38 DIM 27KFL	18.5	1800	97.3	2700K	80	4346	40°
LED17HOP38D27KNFL	LED 18.5W HOP38 DIM 27KNFL	18.5	1800	97.3	2700K	80	9299	25°
LED17HOP38D27KSP	LED 18.5W HOP38 DIM 27KSP	18.5	1800	97.3	2700K	80	21535	15°
LED17HOP38D27KSPB	LED 18.5W HOP38 DIM 27KSP BLACK	18.5	1800	97.3	2700K	80	21535	15°
LED17HOP38D30KFL	LED 18.5W HOP38 DIM 30KFL	18.5	1825	98.6	3000K	80	4365	40°
LED17HOP38D30KFLB	LED 18.5W HOP38 DIM 30KFL BLACK	18.5	1825	98.6	3000K	80	4365	40°
LED17HOP38D30KNFL	LED 18.5W HOP38 DIM 30KNFL	18.5	1825	98.6	3000K	80	12782	25°
LED17HOP38D30KNFLB	LED 18.5W HOP38 DIM 30KNFL BLACK	18.5	1825	98.6	3000K	80	12782	25°
LED17HOP38D30KSP	LED 18.5W HOP38 DIM 30KSP	18.5	1825	98.6	3000K	80	23699	15°
LED17HOP38D30KSPB	LED 18.5W HOP38 DIM 30KSP BLACK	18.5	1825	98.6	3000K	80	23699	15°

NOTE: All items come in shipping cartons of 12.

*continued next page*

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcp.com](http://tcp.com)



# LED PAR Lamps

**DIMMABLE • WET LOCATION • 25,000 HOURS**

ITEM #	DESCRIPTION	WATTS	LUMENS	LPW	COLOR	CRI	MEASURED CBCP	BEAM ANGLE
--------	-------------	-------	--------	-----	-------	-----	---------------	------------

## LED PAR38 HIGH OUTPUT 150W Equivalent Options *continued*

### 18.5W PAR38 High Output • Dimmable • 25,000 Hours • 5.3" (MOI) x 4.8" (DIA)



LED17HOP38D35KFL	LED 18.5W HOP38 DIM 35KFL	18.5	1850	100.0	3500K	80	3481	40°
LED17HOP38D35KFLB	LED 18.5W HOP38 DIM 35KFL BLACK	18.5	1850	100.0	3500K	80	3481	40°
LED17HOP38D35KNFL	LED 18.5W HOP38 DIM 35KNFL	18.5	1850	100.0	3500K	80	11664	25°
LED17HOP38D35KSP	LED 18.5W HOP38 DIM 35KSP	18.5	1850	100.0	3500K	80	23145	15°
LED17HOP38D35KWFL	LED 18.5W HOP38 DIM 35KWFL	18.5	1850	100.0	3500K	80	—	60°
LED17HOP38D41KFL	LED 18.5W HOP38 DIM 41KFL	18.5	1900	102.7	4100K	80	4604	40°
LED17HOP38D41KNFL	LED 18.5W HOP38 DIM 41KNFL	18.5	1900	102.7	4100K	80	11614	25°
LED17HOP38D41KSP	LED 18.5W HOP38 DIM 41KSP	18.5	1900	102.7	4100K	80	22458	15°
LED17HOP38D50KFL	LED 18.5W HOP38 DIM 50KFL	18.5	2000	108.1	5000K	80	4446	40°
LED17HOP38D50KNFL	LED 18.5W HOP38 DIM 50KNFL	18.5	2000	108.1	5000K	80	12467	25°
LED17HOP38D50KSP	LED 18.5W HOP38 DIM 50KSP	18.5	2000	108.1	5000K	80	21535	15°

NOTE: All items come in shipping cartons of 12.

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP AUG 2019/WF164451