



Shown actual size: Skylark® preset dimmer and 1-gang Claro® wallplate in almond (AL)

SKYLARK® dimmers

product family features

- rocker switch returns light to your favorite light level
- slide up to brighten, down to dim (adjust light to suit any activity)
- coordinating Claro® wallplates available separately (including stainless steel)
- **eco-dim®** model available

available models

source type

- incandescent/halogen lighting
- magnetic low-voltage lighting
- electronic low-voltage lighting
- fluorescent lighting
- LED lighting
- dimmable compact fluorescent
- quiet 3-speed fan controls
- quiet 3-speed fan/light controls
- fully variable fan controls

control locations



available colors (see page 12 for color swatches)

colors (gloss finish)

WH white	GR gray
IV ivory	BR brown
AL almond	BL black
LA light almond	

dimmers with on/off switch



- rocker switch turns on/off
- slide up to brighten, down to dim
- eco-dim® model guarantees at least 15% energy savings compared to a standard switch

incandescent/halogen

single pole	600 W	S-600P-	
single pole	1000 W	S-10P-	
3-way	600 W	S-603P-	
3-way	1000 W	S-103P-	

incandescent/halogen — eco-dim®†

NEW

single pole/3-way	600 W	S-603PG-	
-------------------	-------	-----------------	--

magnetic low-voltage

single pole	600 VA (450 W)	SLV-600P-	
3-way	600 VA (450 W)	SLV-603P-	

Suggested maximum lighting load for magnetic low-voltage dimming is 450 W for 600 VA products to allow for transformer losses.

electronic low-voltage*

single pole	300 W	SELV-300P-	
3-way	300 W	SELV-303P-	

requires neutral wire connection

† available in white, ivory, almond, and light almond

dimmers with on/off switch & locator light



- rocker switch turns on/off
- slide up to brighten, down to dim
- includes locator light

incandescent/halogen

single pole	600 W	S-600PNL-	
single pole	1000 W	S-10PNL-	
3-way	600 W	S-603PNL-	
3-way	1000 W	S-103PNL-	

slide-to-off dimmers



- slide up to on/brighten, down to dim/off

incandescent/halogen

single pole	600 W	S-600-	
single pole	1000 W	S-1000-	