



DESCRIPTION

Replace existing metal halide flood fixtures with these more efficient color selectable LED flood fixtures.

FEATURES

- Delivers up to 120 LPW for highly efficient performance
- Slipfitter adjusts up to 180° (90° left and 90° right)
- 0-10V dimming
- 19.69" whip

LISTINGS

- UL rated for wet locations
- IP65
- IK09
- FCC

PERFORMANCE

- CRI: >80
- CCT: 2200K
- LED L70 Life Hours: 50,000 hours
- Bridgelux LEDs

THERMAL

- -31°F to 113°F or (-35°C to 45°C) operating temperature

ELECTRICAL

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Surge Protection: 24kV
- Dimmable power supply (0-10V)

INSTALLATION

- Designed for installation with included slipfitter mount; See installation instructions for more information.

CONSTRUCTION

- Die-cast aluminum housing
- Durable polyester bronze powder coating withstands demanding environments
- Clear impact-resistant tempered glass lens

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Safety and Security Lighting
- Sign Lighting
- Building Facades

PERFORMANCE SUMMARY

Item #	Watts	Lumens	LPW	CCT	Beam Angle	CRI	Dimming	Voltage	Replaces	Mounting	BUG
PLT-13167	105W	12,627	120	2200K	145°	>80	0-10V	120-277V	150W MH	Slipfitter	B4-U0-G1

DIMENSIONS



DIMENSIONS:

Length – 9.1"
 Length (with mount) – 16"
 Width – 11.5"
 Depth – 3.5"
 Weight – 9.08 lbs

PHOTOMETRICS

15W FLOOD FIXTURE

Luminous Intensity Distribution Curve

