

NULS-8/13/18/21/24/28

Low Profile T5 Fluorescent Under Cabinet Fixture

LAMP WATTAGE

- (1) F8T5
- (1) F13T5
- (1) F18T5
- (1) F21T5
- (1) F24T5
- (1) F28T5

DESCRIPTION

T5 Fluorescent slim, low profile under cabinet lighting fixtures ranging in length from 13-1/2" (34cm) to 47" (119cm) and 8 to 28 watts. Ideal for narrow spaces for illuminating window displays

FEATURES

- Efficient T5 Fluorescent Light Source
- Solid State Electronic Ballast
- Flicker-Free Start Up
- Six Available Lengths
- UV Rated One-Piece Clear Diffuser
- UL Listed, Portable Lamp Fixture

HOUSING

.09 Injection Molded White Plastic Construction

MOUNTING

Hardware provided for mounting fixture either to standard horizontal surface or to vertical wall surface.

ELECTRICAL SYSTEM

Sockets accept bi-pin T5 fluorescent light source. Fixture contains recessed male connector for attachment to female receptacle from either 120V power cord or connector from other fixture. Integral solid state ballast for efficient operation.

Rocker switch on side of fixture allows independent on/off control.

Note: 10 fixtures maximum may be connected together on single 120V power cord feed. Do not exceed 10 fixtures per feed.

UL LISTED

UL Listed as Portable Fixture

ACCESSORIES

- NRA-125... Straight Connector (Included with Fixture)
- NRA-125/6 6" Flexible Connector
- NRA-125/12 12" Flexible Connector
- NRA-125/18 18" Flexible Connector



PRODUCT MATRIX

Item No	Lamp	Description
NULS-8	(1) F8T5	13-1/2" (34cm), 8 Watt Fluorescent Under Cabinet Fixture
NULS-13	(1) F13T5	22-1/2" (57cm), 13 Watt Fluorescent Under Cabinet Fixture
NULS-18	(1) F18T5	25-1/8" (64cm), 18 Watt Fluorescent Under Cabinet Fixture
NULS-21	(1) F21T5	35-1/2" (90cm), 21 Watt Fluorescent Under Cabinet Fixture
NULS-24	(1) F24T5	37-1/4" (95cm), 24 Watt Fluorescent Under Cabinet Fixture
NULS-28	(1) F28T5	47" (119cm), 28 Watt Fluorescent Under Cabinet Fixture

DIMENSIONS

ITEM NO	A	B	C
NULS-8	13-1/2" (34cm)	7/8" (22mm)	1-11/16" (43mm)
NULS-13	22-1/2" (57cm)	7/8" (22mm)	1-11/16" (43mm)
NULS-18	25-1/8" (64cm)	7/8" (22mm)	1-11/16" (43mm)
NULS-21	35-1/2" (90cm)	7/8" (22mm)	1-11/16" (43mm)
NULS-24	37-1/4" (95cm)	7/8" (22mm)	1-11/16" (43mm)
NULS-28	47" (119cm)	7/8" (22mm)	1-11/16" (43mm)

