

S48

Specifications:

Maximum Wattage	1000 W
Maximum Voltage	300 V
Maximum Operating Temperature	300° C
Qualifications	UL Recognized – E31557 CSA Certified – LR20904
Body Material	Steatite / Nickel Plated Steel
Contact Material	Screw Shell, Center Contact = Nickel Plated Brass
Wire Leads	AWG 18/16, 600 V/105° C minimum



Single End

ORDERING INFORMATION

Product Number	Product Description	Wire Gauge/Type/Color	Wire Length (inches)	Case / SKU Qty Qty
69668	S48 3IN/18GA/ULSFF1	AWG18/ULSFF1/1 Black, 1 White	3	100 / 100
69663	S48 12IN/18GA/ULSF2	AWG18/ULSF2/1 Black, 1 White	12	100 / 100
69664	S48 14IN/18GA/UL1659	AWG18/UL1659/1 Black, 1 White	14	100 / 100
69665	S48 30IN/18GA/ULSF2	AWG18/ULSF2/1 Black, 1 White	30	100 / 100
69670	S48 36IN/18GA/ULSF2	AWG18/ULSF2/1 Black, 1 White	36	100 / 100
69784	S48 48IN/18GA/ULSF2	AWG18/ULSF2/1 Black, 1 White	48	100 / 20
69669	S48 48IN/18GA/ULSF2	AWG18/ULSF2/1 Black, 1 White	48	100 / 100
69666	S48 72IN/18GA/ULSF2	AWG18/ULSF2/1 Black, 1 White	72	100 / 100

Made-to-order types.

LAMP BASE:

Mini-Candela bra Screw
E11

