



General Specifications

Product Part #	73098	73113	73099
Bulb Type	A19	A19	A19
Base Type	E26	E26	E26
Correlated Color (Kelvin)	2800	4000	6000
Approximate Lumens (Lm)	300	360	360
CRI	>80	>80	>80
Efficacy (Lm/W)	60	72	72
Beam Angle (°)	270°	270°	270°

Electrical Characteristics

Wattage	5W
Voltage	110 - 120VAC 60Hz
Power Factor	>0.8
Dimming	Non-Dimmable
Operating Temperature (°C)	-20° to 45°

Mechanical Specifications

Diameter (inch)	2.53
Height (inch)	4.32
Weight (lbs)	0.25

Lifetime and Warranty

Life to 70% Lumens (hr) LED	29,000
Lifetime (hr) Integral Lamp	25,000
Warranty	3 Years

Ordering and Logistics

Product	UPC
73098	818549010004
73113	818549010011
73099	818549010028
Units per case (Qty. ea.)	20
Case Dimensions (inch)	13.5 x 11 x 5.2
Case Weight (lbs)	7.5
Case Cube (cft.)	0.447

Features and Benefits

- 300 - 360 Lumens
- Consumes up to 85% Less Energy
- Omini-Directional
- Can last over 25,000 hours
- Cool to touch
- Contains No Mercury
- UL Listed
- Shatterproof Design

Applicable Markets

- Residential Lighting
- Commercial Lighting
- Hospitality Lighting

Applications

- Desk Lamps
- Table Lamps
- Floor Lamps
- Sconce Fixtures
- Vanity Lighting Fixtures

LM79-08, LM80-08 and IES files available on request or downloadable from the Viribright website address listed below.

