

# LED

## 4 ft. Single-Ended T8 Tube



### FEATURES

- Compatible with shunted and non-shunted sockets when paired with a compatible ballast
- Equivalent to a 32-Watt fluorescent T8 tube
- 5000 Kelvin Cool White color temperature
- Frosted glass lens evenly diffuses light
- UL listed for use in damp locations
- Bi-Pin G13 base
- DLC® Part Number: PLTSP39114
- NSF/ANSI standard 2 coating

### APPLICATIONS

- Office spaces and work environments
- Kitchens and bathrooms
- Outdoor lighting and garages



ROHS



SKU#

Kelvin

Lumens

CRI

Wattage

Voltage

DLC?

Base

Life Hours

Warranty

PLT-90034

5000

1800

82

12

120-277

YES

Bi-Pin

50,000

5 Year

### SPECIFICATIONS

DIMMABLE .....	NO	LUMENS .....	1,800
DLC LISTED .....	YES	VOLTAGE .....	120-277
SAFETY RATING .....	UL DAMP	LENS .....	FROSTED GLASS
CRI .....	82	BASE TYPE .....	G13
COLOR .....	DAYLIGHT WHITE	OPERATION .....	PLUG AND PLAY
COLOR TEMPERATURE .....	5000K	DIAMETER .....	1 IN.
LIFE HOURS .....	50,000	LENGTH .....	48 IN.
SYSTEM WATTAGE (INCLUDING BALLAST) .....	15 WATTS	FLUORESCENT EQUAL.....	32 WATT