

LED T8 FIXTURES

LIGHTING THE FUTURE

PLT LED Ready Fixtures are high quality, dedicated to the LED lamp technology for efficiency and optimal performance. They consume up to 80% less energy, significantly reducing operating costs and are environmentally friendly. The construction allows excellent heat dispersion and convenient installation.

- **CONSTRUCTION**

Die form cold-rolled steel housing

- **FINISH**

White powder coat, 86% minimum average reflective

- **OPTICS**

Designed to optimize lamp performance and light output.

- **FEATURES**

Troffer: Spring loaded cam latches • Mitered and fully gasketed door frame • Acrylic prismatic lens

Direct/Indirect: Perforated diffuser

General Purpose Wrap: Acrylic prismatic lens

Parabolic: Low glare illumination

All fixtures have Non-Shunted Sockets



TROFFER



18 CELL PARABOLIC



DIRECT/INDIRECT



STRIP



WRAP



VAPOR TIGHT



HORIZON HIGH BAY



DIAMOND HIGH BAY

Ordering Information

ITEM#	DESCRIPTION	NO. OF LAMPS	TYPE OF LAMPS	VOLTS	CASE
LED INTERIOR FIXTURES					
55027	LED 48" STRIP FIXTURE FOR 2 T8	2	T8	--	1
55028	LED 96" TANDEM STRIP FIXTURE FOR 4 T8	4	T8	--	1
55029	LED 48" WRAP A ROUND FOR 2 T8	2	T8	--	1
55044	LED 2 X 4 TROFFER FOR 2 T8	2	T8	--	1
55046	LED 2 X 4 TROFFER FOR 3 T8	3	T8	--	1
55048	LED 2 X 4 TROFFER FOR 4 T8	4	T8	--	1
55050	LED 2 X 4 18 CELL FOR 3 T8	3	T8	--	1
55042	LED 2 X 4 RECESSED DIRECT/INDIRECT FOR 2 T8	2	T8	--	1
LED HIGH BAYS					
55054	LED DIAMOND HIGH BAY™ FOR 4 T8	4	T8	--	1
55056	LED DIAMOND HIGH BAY™ FOR 6 T8	6	T8	--	1
55058	LED DIAMOND HIGH BAY™ FOR 8 T8	8	T8	--	1
55060	LED HORIZON HIGH BAY™ FOR 4 T8	4	T8	--	1
55062	LED HORIZON HIGH BAY™ FOR 6 T8	6	T8	--	1
LED VAPOR TIGHT					
57739	LED VAPOR TIGHT FOR 2 T8/CLEAR LENS	2	T8	--	1
57742	LED VAPOR TIGHT FOR 3 T8/CLEAR LENS	3	T8	--	1
57746	LED VAPOR TIGHT FOR 4 T8/CLEAR LENS	4	T8	--	1
57741	LED 96" TANDEM VAPOR TIGHT FOR 4 T8/CLEAR LENS	4	T8	--	1
LED LINEAR TUBES					
		COLOR	LUMENS	VOLTS	CASE
90524	LED SMD 4' 15WT8/40K/FR/V4 - DLC	4000K	1800	120-277V	25
90540	LED SMD 4' 15WT8/50K/FR/V4 - DLC	5000K	1850	120-277V	25
90535	LED SMD 4' 18WT8/35K/FR/V4 - DLC	3500K	1800	120-277V	25
90537	LED SMD 4' 18WT8/40K/FR/V4 - DLC	4000K	1850	120-277V	25
90539	LED SMD 4' 18WT8/50K/FR/V4 - DLC	5000K	1900	120-277V	25
90692	LED SMD 4' 18WT10/CL/30K/120V/DIMMABLE	3000K	1600	120V	25
90688	LED SMD 4' 18WT10/CL/40K/120V/DIMMABLE	4000K	1650	120V	25
90639	LED SMD 4' 18WT10/CL/50K/120V/DIMMABLE	5000K	1700	120V	25

