



# LED PL Lamps - Hybrid

## DESCRIPTION

Reduce your energy costs by replacing CFL PL lamps with these more efficient hybrid LED PL lamps that can operate with or without a ballast.

## FEATURES

- Frosted lens reduces visual glare
- Delivers up to 145 Lumens per Watt for highly efficient performance
- Replaces up to a 18W CFL lamp
- Universal burn position
- No rewiring or modifications of any kind required for plug-and-play (Type A) operation; must be used with a compatible ballast, see installation sheet for full list of compatible ballasts
- Can operate directly off line voltage for ballast bypass (Type B) operation; ballast must be removed and fixture rewired during installation; see installation instructions for more information
- Only operates on magnetic ballasts listed in compatibility list. See installation sheet for full list of compatible ballasts

## LISTINGS

- UL Listed for damp locations
- IP20
- FCC Part 15 Class B
- RoHS

## PERFORMANCE

- CRI: 80
- CCT: 4000K
- LED L70 Life Hours: 50,000 hours

## THERMAL

- - 4°F to 113°F (-20°C to 45°C) operating temperature

<b>Project name</b>	<b>Type</b>
<b>Catalog number</b>	
<b>Comments</b>	<b>Voltage</b>
<b>Approved by</b>	<b>Date</b>



## WARRANTY

- 5-year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details

## APPLICATIONS

- Recessed Cans
- Ceiling Fixtures
- Wall Sconces

<b>PERFORMANCE</b>	<b>Power Consumption</b>	5, 7 Watt
	<b>Lumens</b>	721, 976
	<b>Efficacy (LPW)</b>	139, 145
	<b>CRI</b>	80
	<b>CCT</b>	4000K
	<b>LED L70 Life Hours</b>	50,000
<b>ELECTRICAL</b>	<b>Input Voltage</b>	120-277V
	<b>THD</b>	20%
	<b>Power Factor</b>	0.9
	<b>Surge Protection</b>	500V
	<b>Burn Position</b>	Universal
<b>CONSTRUCTION</b>	<b>Shape</b>	PL
	<b>Base</b>	G24D
	<b>Lens</b>	Plastic
	<b>Finish</b>	Frosted
	<b>Certifications</b>	UL Listed, IP20
<b>LISTINGS</b>	<b>Material Usage</b>	
	<b>Environment</b>	Damp Locations

\* See Selectable Table for full breakdown

## PERFORMANCE SUMMARY

Item #	Base*	Wattage	Lumens	LPW	CCT	Voltage	Replaces	CRI	Finish	LED L70 Life Hours	Dimmable	Burn Position
PLT-20326	GX23	7	976	139	4000K	120-277V	13-18W CFL	80	Frosted	50,000	No	Universal
PLT-20327	G23	5	721	145	4000K	120-277V	7 to 9W CFL	80	Frosted	50,000	No	Universal
PLT-20328	G24D	7	976	139	4000K	120-277V	13-18W CFL	80	Frosted	50,000	No	Universal
PLT-20329	G24D	5	721	145	4000K	120-277V	9W CFL	80	Frosted	50,000	No	Universal

\*See Compatible Sockets for a full breakdown


## COMPATIBLE SOCKETS

SKU	Compatible Sockets	Non-Compatible Sockets
PLT-20326	GX23, GX23-2, G24d-2, G24q-1, GX24q-1, G24q-2, GX24q-2	n/a
PLT-20327	G23	n/a
PLT-20328	GX23, GX23-2, G24d-2, G24q-1, GX24q-1, G24q-2, GX24q-2	G24q-5/6/7, GX24q-5/6/7
PLT-20329	G23, G23-2, 2G7, G24Q-1, GX24Q-1, G24Q-2, GX24Q-2	G24q-5/6/7, GX24q-5/6/7

## DIMENSIONS

### **PLT-20326**

Height – 4.76"  
Diameter – 1.52"




### **PLT-20327**

Height – 4.13"  
Diameter – 1.52"




### **PLT-20328**

Height – 4.53"  
Diameter – 1.52"



### **PLT-20329**

Height – 3.9"  
Diameter – 1.52"



## WARNINGS

- Not for use with dimmers
- Not for use in enclosed fixtures.