



**DESCRIPTION**

Replace existing fluorescent troffers with these LED ready troffers designed for use with direct wire LED T8 tubes.

**FEATURES**

- Cost-effective architectural recessed LED ready troffer
- One to one alternative LED solution for fluorescent troffers
- Utilizes 4 single-ended direct wire LED T8 tubes (Sold Separately)
- Perfect for general illumination and provides visual comfort with minimal glare

**LISTINGS**

- UL Listed for damp locations
- IP20
- RoHS

**ELECTRICAL**

- Input voltage: 120-277V
- Pre-wired non-shunted sockets

**INSTALLATION**

- Designed for recess mounting in T-grid or dropped ceilings; see installation instructions for more information

**CONSTRUCTION**

- Galvanized steel housing
- Acrylic lens

**THERMAL**

- -4°F to 104°F operating temperature

<b>Project name</b>	<b>Type</b>
<b>Catalog number</b>	
<b>Comments</b>	<b>Voltage</b>
<b>Approved by</b>	<b>Date</b>



**WARRANTY**

- 5-year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details

**APPLICATIONS**

- Conference Rooms
- Retail
- Offices
- Hospitality
- Healthcare
- Schools
- Receptions Areas
- Corridors
- Foyers

<b>ELECTRICAL</b>	<b>Lamp Type (Not Included)</b>	T8 Single End Direct Wire LED Lamps
	<b>Number of Lamps</b>	4
	<b>Max. Wattage per Tube</b>	24.5W
	<b>Input Voltage</b>	120-277V
<b>CONSTRUCTION</b>	<b>Housing</b>	Galvanized steel
	<b>Lens</b>	PMMA
	<b>Base Power Supply</b>	Hard wired for Single-ended Direct Wire T8 LED Lamps
	<b>Finish</b>	White
<b>LISTINGS</b>	<b>Certifications</b>	UL Listed, IP20, RoHS
	<b>Operating Temperature</b>	-4°F to 104°F
	<b>Environment</b>	Damp Locations

## PERFORMANCE SUMMARY

Item #	Length	Width	Height	Max. Wattage per Tube	Voltage	Warranty	Compatible Lamps
PLT-80104	47.8"	23.8"	3.3"	24.5W	120-277V	5-years	Single-ended Direct Wire T8 LED Lamps

## DIMENSIONS



### **DIMENSIONS:**

Length – 47.8"

Height – 3.3"

Width – 23.8"

Weight – 19 lbs.