



LED

DUAL MODE TUBES



## PRODUCT FEATURES

- Direct Replacement / Plug & Play Mode (Type A) \*
- Retrofit / Bypass Mode - Double and Single Ended (Type B)
- Bypass installation utilizes existing lamp holders
- Film Coated Shatter Resistant Glass Tube
- Frosted & Clear Applications Available
- Instant On / No Flicker
- Non-Dimming
- IP20 Rated
- 120-277 Voltage Rating, PF > 0.9
- 80+ CRI
- G13 Mounting
- Aluminum End Caps
- UL Classified & UL Listed
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature: -4°F to 113°F (-20°C to 45°C)

\* See Ballast Compatibility Chart

## PRODUCT SPECIFICATIONS

| MODEL               | ITEM #         | POWER (W) | LUMENS (LM) | CCT (K) | LENGTH (IN) | DIFFUSER    | BEAM ANGLE |
|---------------------|----------------|-----------|-------------|---------|-------------|-------------|------------|
| CLT94-18WT8AM-40-AB | L18T84KABCL94  | 18        | 2300        | 4000    | 48.0        | Frosted     | 220°       |
| CLT94-18WT8AM-50-AB | L18T85KABCL94  | 18        | 2300        | 5000    | 48.0        | Frosted     | 220°       |
| CLT94-18WT8AT-50-AB | L18T85KCABCL94 | 18        | 2300        | 5000    | 48.0        | Transparent | 220°       |

