



PYCC-1M1UNV115S-50D

Selectable Constant Current LED Driver

- Input Voltage: 120V - 277V, 50/60Hz
- Selectable Output Current
- Class 2 LED Driver
- Class P
- Isolated 0-10V Dimming
- Suitable for Dry and Damp location

General Specifications

Input Voltage / Frequency	120V - 277VAC 50/60Hz
Input Current	0.56A Max.
Input Power	67W Max.
Input Power Factor	>0.90
THD	<20%
Driver Type	Dimmable, Isolated
Output Voltage Range	30V - 45V $\bar{=}$
Selectable Output Current	1050mA, 1100mA, 1150mA ($\pm 5\%$)
Output Power	51.75W Max.
Uout	< 60V
Efficiency	86% Typ.
Output Type	Constant Current
Inrush Current	60A @277VAC
Max. Leakage Current	0.75mA
Total Over All Ripple	<30%
Flicker Percentage	30%
Dimming Type	0-10V
Dimming Range	100% - 10%
Dimming isolation	Yes
Operating Ambient Temperature Range	-25°C - 50°C
Tc	90°C
Start Up Time	0.5s
Number of Output Channels	1
Overall Size	11.043"x 1.18"x 0.846"
Weight	0.46lbs (210g)
Wire Type / Length	Input: 18AWG / 12" Output & Dimming: Termial block
Standards / Compliance	UL 8750,UL1310 CSA C22.2 No.250.13, FCC Part 15B
IP Rating	IP20
Operating Humidity	10-90% RH Non-condensing
Input Surge Protection	Line-Neutral 1kV, Line & Neutral-Ground 2kV, RingWave 2.5kV
Protections	Over-Voltage Protection Short-Circuit Protection
Sound Rating	A
Service Life	50,000Hrs @Max Load, 85°C Tc
Warranty	5 years @ Tc 85°C from the date of manufacture

General Wiring Diagram













PYCC-1M1UNV115S-50D



Typical Characteristics Curve





FC



UL
LISTED
E342838

P Y C C 1 M 1 UNV 115 S 50 D

Page 3 of 5
2024-980 Rev A



PYCC-1M1UNV115S-50D



Guidelines

Grounding

- Driver must be grounded by means of the Driver case.

LED load

- The Fulham Pony LED drivers are designed to drive passive LEDs, -COB's and -LED assemblies. Proper function is not guaranteed when (LED) loads with active components are used.

Short-circuit protection

- In case of a short circuit the LED driver switches to protection mode. After the removal of the short-circuit the LED driver will recover automatically.

No-load Operation

- In no-load operation the output voltage will not exceed the specified open circuit output voltage.

Hot Swapping

- This driver does not support hot swapping of the LEDs.

Remote Mounting

- Up to 26ft with 18AWG. Contact Fulham for higher remote distance.

Service life/Lifetime

- Failure Rate Info based upon MTBF modeling: 90% survivals at end of life @ $\leq T_c$ lifetime rating.

Warranty

- Reference Fulham's limited Warranty: <https://cdn.fulham.com/PDFs/Limited-Warranty.pdf>



PYCC-1M1UNV115S-50D



RoHS
COMPLIANT




Product Image:

PYCC-1M1UNV115S-50D



Packaging

Master Carton



OUTER DIMENSION		
L	W	H
18.26" (464mm)	12.56"(319mm)	7.05" (179mm)
Net Weight	Gross Weight	QUANTITY
26.68bs. (12.1kg.)	29.76lbs. (13.5kg)	55pcs.