





LED R20/30/40 Reflector Shape Dimmable Light Bulb

LED DIMMABLE Reflector R20

Nominal Wattage	Overdrive Model #	Description	Initial Lumen	Lm/watt	Power Factor	CRI	Average Rated Life (Hrs.)	Dia Inch	Length Inch	Case Qty	Equal Incand.	Item #
7	•L7R20DIM/30K	7W LED R20 Shape Bulb Dimmable - 3000K	540	77	0.97	82	25,000	2.48 / 63	3.9 / 100	12	= 50W	597
	■L7R20DIM/50K	7W LED R20 Shape Bulb Dimmable - 5000K	580	83	0.97	82	35,000	2.48 / 63	3.9 / 100	12	= 50W	604
	•L8R20DIM/30K	8W LED R20 Shape Bulb Dimmable - 3000K	520	65	0.70	82	25,000	2.48 / 63	3.9 / 100	12	= 50W	525
	■L8R20DIM/50K	8W LED R20 Shape Bulb Dimmable - 5000K	560	70	0.70	82	35,000	2.48 / 63	3.9 / 100	12	= 50W	568

LED DIMMABLE Reflector R30

Nominal Wattage	0.10101110	Description	Initial Lumen	Lm/watt	Power Factor	CRI	Average Rated Life (Hrs.)	Dia Inch	Length Inch	Case Qty	Equal Incand.	Item #
8.5 9 9 10	•L8R30DIM/30K •L9R30DIM/27K •L9R30DIM/50K •L10R30DIM/50K •L10HR30DIM/27K	8.5W LED R30 Shape Bulb Dimmable - 3000K 9W LED R30 Shape Bulb Dimmable - 2700K 9W LED R30 Shape Bulb Dimmable - 5000K 10W LED R30 Shape Bulb Dimmable - 5000K 10W LED 90 CRI BR30 Reflector Dim - 2700K	670 650 730 800 670	79 72 81 80 67	0.95 0.99 0.99 0.99 0.99	82 82 82 82 90	25,000 25,000 25,000 35,000 25,000	3.74 / 95 3.74 / 95 3.74 / 95 3.74 / 95	5.2 / 130 5.2 / 130 5.2 / 130 5.1 / 130 5.2 / 130	12 12 12	= 65W = 65W = 65W = 65W	598 544 545 588 570

LED DIMMABLE Reflector R40

Nominal Wattage	5.151.511.15	Description	Initial Lumen	Lm/watt	Power Factor	CRI	Average Rated Life (Hrs.)	Dia Inch	Length Inch	Case Qty	Equal Incand.	Item #
12 13 13 17 18 18	•L12R40DIM/30K •L13R40DIM/30K •L13R40DIM/50K •L17R40DIM/30K •L18R40DIM/30K •L18R40DIM/50K	12W LED R40 Shape Bulb Dimmable - 3000K 13W LED R40 Shape Bulb Dimmable - 3000K 13W LED R40 Shape Bulb Dimmable - 5000K 17W LED R40 Shape Bulb Dimmable - 3000K 18W LED R40 Shape Bulb Dimmable - 5000K	930 880 950 1230 1230 1320	78 68 73 72 68 73	0.97 0.90 0.90 0.98 0.90 0.90	82 82 82 82 82 82	25,000 25,000 35,000 25,000 25,000 35,000	5.0 / 127 5.0 / 127 5.0 / 127 5.0 / 127 5.0 / 127 5.0 / 127	6.5 / 164 6.5 / 164 6.5 / 164 6.5 / 164 6.5 / 164	12 12 12 12 12 12	= 70W = 85W = 85W = 85W = 120W = 120W	599 528 529 600 526 527

•LM79/LED LISTED (LIGHTING DESIGN LAB)

• ENERGY STAR LISTED

Applications















Fully Dimmable



Features

- Designed for long product life electronics and LEDs
- Instantly bright and color stability over lifetime of product
- Environmentally friendly mercury free & lead free
- Maintenance free for more than ten years (assuming 8 hours per day 365 days per year)
- Significantly reduces maintenance costs
- Intelligently and aesthetically designed
- Low energy consumption Save up to 80% in energy cost
- Direct replacement and easy to fit
- Instant On Light



- Available in other color temperature also (upon request)
- Dimension with + 0.1 inch tolerance
- Lumen Maintenance (L70>25,000 hrs.)
- Specifications can be changed without prior notice, as LED is a dynamic & new evolving technology
- <u>CAUTION</u>: The lamp may not be compatible with all dimmer. Check www.overdrive-lighting.com or www.overdriveasia.com to find up to date dimmer compatibility option.















