

LED

Panels




FEATURES

- Equipped standard with a 0-10V continuous dimming driver that's compatible with 0-10V controllers/dimmers
- Unique optics guide plate controls glare and provides uniform light distribution
- Long life, 60,000 hour LEDs at L80 reduce life cycle maintenance costs
- Low profile aluminum housing, 2" depth including transformer panel
- Fits standard T-Bar and narrow grid drop ceiling
- ETL damp location rated




SKU #	Kelvin	Lumens	Size	Wattage	Voltage	DLC?	Mounting	Life Hours	Warranty
PLTG1113	5000	4413	1X4	40	120-277	YES	CEILING	60000	5 years

ADDITIONAL PHOTOS



1' x 4' Edge-Lit LED Panel
Width: 11.75"
Length: 47.75"
Height: 0.35"
2.35" w/ Driver mounted



FEATURES

- Extruded aluminum housing
- Smooth opalescent acrylic lens
- Suspended/surface mounting accessories sold separately

TYPICAL APPLICATIONS

- Schools, Factories, Hotels
- Office, Conference Rooms
- Hospitals

WARRANTY

Warranty

5 Years

SPECIFICATIONS

Dimmable	Yes
DLC Listed	Yes
Safety Rating	ETL
CRI	80
Color.....	Daylight White
Color Temperature.....	5000 Kelvin
Life Hours	60,000
Wattage	40 Watt
Lumens.....	4413
Voltage	120-277
Finish.....	White
Housing	Aluminum
Mounting	Ceiling Grid Mount
Lens	Opaque
Length	47.75 in.
Height	0.35 in.
Width	11.75in.
Weight.....	7 lbs.
Warranty.....	5 Years