

08/16/19

CONTROLLED

CD AERO CONFIDENTIAL INFORMATION NOTICE: This document is the property of CD Aero and is delivered on the express condition that it is not to be disclosed, reproduced in whole or in part, or used for manufacture for anyone other than CD Aero without written consent; and that no right is granted to disclose or use any information contained in this document.

| REVISION | LTR | DATE | APPR |
|----------------------|-----|-----------|------|
| Update per DCN 17576 | BE | 8/15/2019 | CWF |
| Update per DCN 17565 | BD | 8/7/2019 | CWF |
| Update per DCN 17389 | BC | 7/24/2018 | LJS |



Must be RoHS COMPLIANT

MUST BE ROHS COMPLIANT

| | |
|-------------|-----------------|
| DRAWN BY | G.GRENIER |
| CHECKED BY | J.Ryall |
| APPROVED BY | E.Labo |
| USED ON | DRY PLASTIC HID |

| | |
|----------|------------|
| DATE | 5/10/2008 |
| DATE | 5/12/2009 |
| DATE | 5/12/2009 |
| TITLE | CD Aero |
| DWG. NO. | 49981-1450 |

| Part Number | CDE P/N (REF) | Rated Capacitance | Cap Tolerance | Rated Voltage | MAX TEMP | OD (+/- .06 inches) | HT (+/- .06 inches) | Dielectric T (u) | Standard Resistance | Wire Style | REV | MAX DF @ 1KHZ | Customer Part Number Label Marking Requirement |
|--------------|---------------|-------------------|---------------|---------------|----------|---------------------|---------------------|------------------|---------------------|------------|-----|---------------|--|
| D83W3014M01H | 4167-P | 14 | ±3% | 300 | 105°C | 1.58 | 2.68 | 6.8 | 1.0 Meg | 1 | C | 0.00255 | - |
| D83W3022M01H | 4674-P-HT | 22.5 | ±3% | 300 | 105°C | 1.58 | 3.62 | 6.8 | 1.0 Meg | 1 | A | 0.00471 | - |
| D83W3308M01H | 4406-P | 8 | ±3% | 330 | 105°C | 1.58 | 2.68 | 6.8 | 2 Meg | 1 | C | 0.00198 | - |
| D83W3310M01H | 4408-P | 10 | ±3% | 330 | 105°C | 1.58 | 2.68 | 6.8 | 2 Meg | 1 | C | 0.00217 | - |
| D83W3312M01H | 4411-P | 12 | ±3% | 330 | 105°C | 1.58 | 2.68 | 6.8 | 2 Meg | 1 | C | 0.00236 | - |
| D83W3312M01H | 4608-P | 12.5 | ±3% | 330 | 105°C | 1.58 | 2.68 | 6.8 | 2 Meg | 1 | C | 0.00240 | - |
| D83W3314M01H | 4129-P | 14 | ±3% | 330 | 105°C | 1.58 | 2.68 | 6.8 | 1.0 Meg | 1 | D | 0.00255 | - |
| D83W3316M01H | 4421-P | 16 | ±3% | 330 | 105°C | 1.58 | 2.68 | 6.8 | 1.0 Meg | 1 | D | 0.00273 | - |
| D83W3317M01H | 4424-P-HT | 17.5 | ±3% | 330 | 105°C | 1.58 | 3.62 | 6.8 | 1.0 Meg | 1 | E | 0.00287 | 11799283 |
| D83W4008M01H | 4620-P | 8 | ±3% | 400 | 105°C | 1.58 | 2.68 | 8.8 | 2 Meg | 1 | A | 0.00175 | CE433X08R2 |
| D83W4010M01H | 4616-P | 10 | ±3% | 400 | 105°C | 1.58 | 3.62 | 8.8 | 2 Meg | 1 | D | 0.00296 | 1092-007501-101 |
| D83W4011M01H | 4630-P | 11 | ±3% | 400 | 105°C | 1.58 | 3.62 | 8.8 | 2 Meg | 1 | C | 0.00306 | HHMHDCAP175 |
| D83W4012M01H | 4711-P | 12 | ±3% | 400 | 105°C | 1.58 | 3.62 | 8.8 | 1.0 Meg | 1 | C | 0.00336 | - |
| D83W4014M01H | 4164-P | 14 | ±3% | 400 | 105°C | 1.58 | 3.62 | 8.8 | 1.0 Meg | 1 | E | 0.00345 | - |
| D83W4015M01H | 4617-P | 15 | ±3% | 400 | 105°C | 1.58 | 3.62 | 8.8 | 0.5 Meg | 1 | E | 0.00816 | - |
| D84W2448M01H | 4461-P | 48 | ±3% | 240 | 105°C | 1.77 | 3.62 | 4.8 | 0.5 Meg | 1 | A | 0.00816 | - |
| D84W2452M01H | 4464-P | 52 | ±3% | 240 | 105°C | 1.77 | 3.62 | 4.8 | 0.5 Meg | 1 | B | 0.00855 | 058-52-65080 |
| D84W2455M01H | 4465-P | 55 | ±3% | 240 | 105°C | 1.77 | 3.62 | 4.8 | 0.5 Meg | 1 | B | 0.00885 | - |
| D84W2456M01H | 4467-P | 56 | ±3% | 240 | 105°C | 1.77 | 3.62 | 4.8 | 0.5 Meg | 1 | A | 0.00895 | - |
| D84W2460M01H | 4693-P-HT | 60 | ±3% | 240 | 105°C | 1.77 | 3.62 | 4.8 | 0.5 Meg | 1 | A | 0.00830 | - |
| D84W2462M01H | - | 62 | ±3% | 240 | 105°C | 1.77 | 3.62 | 4.8 | 0.33 Meg | 1 | A | 0.00953 | - |
| D84W2848M01H | 4621-P | 46 | ±3% | 280 | 105°C | 1.77 | 3.62 | 5.8 | 0.5 Meg | 1 | A | 0.00741 | - |
| D84W2848M01H | 4462-P-HT | 48 | ±3% | 280 | 105°C | 1.77 | 3.62 | 5.8 | 0.5 Meg | 1 | D | 0.00760 | - |
| D84W3040M01H | 4724-P | 40 | ±3% | 300 | 105°C | 1.77 | 4.61 | 6.8 | 0.5 Meg | 1 | C | 0.00642 | - |
| D84W3055M01H | 4466-P | 55 | ±3% | 300 | 105°C | 1.77 | 4.61 | 5.8 | 0.33 Meg | 1 | B | 0.00990 | - |
| D84W3326M01H | 4444-P | 26 | ±3% | 330 | 105°C | 1.77 | 3.62 | 6.8 | 0.82 Meg | 1 | B | 0.00505 | - |
| D84W4016M01H | 4670-P | 16 | ±3% | 400 | 105°C | 1.77 | 3.62 | 8.8 | 1.0 Meg | 1 | A | 0.00355 | CE434X02R1 |
| D84W4017M01H | 4704-P-HT | 17 | ±3% | 400 | 105°C | 1.77 | 3.62 | 8.8 | 1.0 Meg | 1 | A | 0.00370 | 11889758 |
| D84W4017M01H | N/A | 17.5 | ±3% | 400 | 105°C | 1.77 | 3.62 | 8.8 | 1.0 Meg | 1 | D | 0.00370 | - |
| D84W4018M01H | 4664-P-HT | 18 | ±3% | 400 | 105°C | 1.77 | 3.62 | 8.8 | 1.0 Meg | 1 | E | 0.00375 | 11768278 |
| D84W4021M01H | N/A | 21 | ±3% | 400 | 105°C | 1.77 | 3.62 | 8.8 | 1.0 Meg | 1 | D | 0.00404 | - |
| D85W4024M01H | 4618-P | 24 | ±3% | 400 | 105°C | 1.97 | 4.61 | 8.8 | 0.82 Meg | 1 | E | 0.00581 | - |
| D85W4024M01H | 4662-P | 20.5 | ±3% | 400 | 105°C | 1.97 | 3.70 | 8.8 | 1.0 Meg | 1 | A | 0.00399 | CA20.5400 |
| D85W4026M01H | 4657-P | 26 | ±3% | 400 | 105°C | 1.97 | 3.70 | 8.8 | 0.82 Meg | 1 | B | 0.00453 | CE460X01R3 |
| D85W4028M01H | 4708-P-HT | 28 | ±3% | 400 | 105°C | 1.97 | 4.61 | 8.8 | 0.82 Meg | 1 | B | 0.00622 | - |
| D85W4030M01H | - | 30 | ±3% | 400 | 105°C | 1.97 | 4.61 | 8.8 | 0.79 Meg | 1 | B | 0.00642 | - |