

LED

4 ft. Plug-and-Play T8 Tube



FEATURES

- Suitable replacement for 32-Watt T8 and 34 or 40-Watt T12 fluorescent tubes
- Operates with an existing electronic ballast
- Can be used with shunted and non-shunted sockets with compatible ballasts
- UL listed for damp locations
- Has a Bi-Pin G13 base
- DLC® Part Number: PLTSP39114

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90016	4 ft.	2200	15W	4000K	Plug-and-Play	82	YES	Medium Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T8	LIFE HOURS	50,000
DIMMABLE	NO	FLUORESCENT EQUAL	32-WATT
SAFETY RATING	UL DAMP	COMPATIBILITY	ELECTRONIC BALLASTS
COLOR	COOL WHITE	LAMPHOLDER(S)	SHUNTED & NON-SHUNTED
LIFE HOURS	50,000	LENS	FROSTED GLASS
SYSTEM WATTAGE (INCLUDING BALLAST)	18W	LENGTH	47.67 IN.
VOLTAGE	120-277	DIAMETER	0.98 IN.